

MICHIGAN CHROME & CHEMICAL COMPANY. -- MICRO PRIMER (C-1452/WHITE). --
8010-01-046-5096

=====
===== Product Identification =====

Product ID:MICRO PRIMER (C-1452/WHITE).
MSDS Date:01/01/1987
FSC:8010
NIIN:01-046-5096
MSDS Number: BGHPW
=== Responsible Party ===
Company Name:MICHIGAN CHROME & CHEMICAL COMPANY.
Address:8615 GRINNELL AVE
City:DETROIT
State:MI
ZIP:48213-1152
Country:US
CAGE:01058
=== Contra
ctor Identification ===
Company Name:MICHIGAN CHROME AND CHEMICAL CO
Address:8615 GRINNELL AVE
Box:City:DETROIT
State:MI
ZIP:48213-1152
Country:US
CAGE:01058

=====
===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 64.4%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)
CAS:110-8

0-5
RTECS #:KK8050000
Fraction by Wt: 4.7%
OSHA PEL:S,200 PPM
ACGIH TLV:S, 5 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 20.9%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LACTOL SPIRITS.
Fraction by Wt: 10%
ACGIH TLV:300 PPM

=====
Hazards Identification
=====

Effects of Overexposure:NAUSEA,DIZZINESS,HEADACHES,POSSIBLE DRYING OR CHAPPING HANDS.

=====
First Aid Measures
=====

First Aid:INH:REMOVE TO FRESH AIR,SEE PHYSICIAN IF SYMPTOMS PERSIST;EYE:FLUSH WITH WATER;SKIN:WIPE OFF SOLVENT,WASH WITH SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:26F/-3.3C(COC)
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP
Unusual Fire/Explosion Hazard:TREAT SAME AS LACQUE R OR PAINT
FIRE.EXTREME HEAT BURNS WITH BLACK SMOKE;FUMES CAN FORM EXPLO MIXTURE

=====
Accidental Release Measures
=====

Spill Release Procedures:DIKE AREA-KEEP SPARKS OR FLAME FROM SPILL AREA.WIPE UP OR SOAK UP WITH SAND OR ABSORBENT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:WEAR GOGGLES TO PROTECT FROM SPLASHING. STORE OUT OF DIRECT SUNLIGHT.LET WARM TO 60F BEFORE USING IN W

INTER.

Other Precautions:NO SMOKING IN AREA- STORE AWAY FROM OPEN FLAME AT RM TEMP.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR MASK.
Ventilation:GOOD VENTILATION.
Protective Gloves:RECOMMENDED
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:AVOID SKIN CONTACT.
Supplemental Safety and Health
MSDS DATED 3-10-87.

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:NA
Vapo
r Pres:NA
Vapor Density:NA
Spec Gravity:0.91
Solubility in Water:15-17 WT%
Appearance and Odor:MILKY LIQUID,STRONG SOLVENT ODOR.
Percent Volatiles by Volume:83.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CO,CO*2.SMOKE.

===== Disposal Considerations =====

Waste Disposal Methods:CAN BE INCINERATED OR DISPOSED OF IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility

for the suitability of this information to their particular situation.