

CAPTREE CHEMICAL CO. -- LIQUID CAUSTIC SODA,50% -- 6810-01-051-3050

=====
Product Identification
=====

Product ID:LIQUID CAUSTIC SODA,50%

MSDS Date:01/01/1987

FSC:6810

NIIN:01-051-3050

MSDS Number: BGJCG

=== Responsible Party ===

Company Name:CAPTREE CHEMICAL CO.

Address:445 WINDING RD

City:OLD BETHPAGE

State:NY

ZIP:11804

Country:US

Info Phone Num:516-752-9808

Emergency Phone Num:516-752-9808

CAGE

:1U973

=== Contractor Identification ===

Company Name:CAPTREE CHEMICAL CORP.

Address:32-B NANCY STREET

Box:City:WEST BABYLON

State:NY

ZIP:11704

Country:US

Phone:516-491-7400

CAGE:1U973

=====
Composition/Information on Ingredients
=====

Ingred Name:SODIUM HYDROXIDE (SARA III)

CAS:1310-73-2

RTECS #:WB4900000

Fraction by Wt: 50%

OSHA PEL:2 MG/M3

ACGIH TLV:C 2 MG/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

===

Health Hazards Acute and Chronic: EYE-SEVERE BURNS; SML QTY CAN RESULT IN PERM DAMAGE/SIGHT LOSS. SKIN-BURNS, DEEP ULCERATION, ULTIMATE SCARRING-DESTROYS TISSUE, MIST-DERMATITIS. INHAL-CAN RANGE FM MILD IRRIT OF MUCOUS MEMBRANES TO SEVERE PNEUMONITIS. INGEST-CAN CAUSE SERIOUS DAMAGE TO MOUTH, ESOPHAGUS, STOMACH, OTHER TISSUES, CAN BE FATAL.

Effects of Overexposure: SEE HEALTH HAZARDS

=====
===== First Aid Measures =====

First Aid: EYES-FLUSH W/WATER 15 MIN; SEE PHYSICIAN. SKIN-REMOVE CONTAM CLOTH, SHOES; IMMEDIATELY FLUSH W/WATER-CONTINUE TIL SLICK FEELING IS GONE. INHAL-GET TO FRESH AIR; GIVE ARTIFICIAL RESPIR IF REQD; CALL PHYSICIAN. INGEST -IF CONSCIOUS GIVE QT WATER; DO NOT INDUCE VOMIT. IMMEDIATELY TAKE TO PHYS/HOSPITAL.

=====
===== Fire Fighting Measures =====

Flash Point: NONE
Unusual Fire/Explosion Hazard: CONTACT W/SOME METALS, PARTICULARLY MAGNESIUM ALUMINUM & GALVANIC ZINC CAN GENERATE HYDROGEN RAPIDLY, WHICH IS EXPLOSIVE.

=====
===== Accidental Release Measures =====

Spill Release Procedures: DIKE AREA TO CONTAIN SPILL. PERMIT ONLY TRAINED PERS W/PROPER PROTECT EQUIP IN AREA. RECLAIM IF POSS OR DILUTE SPL W/WATER & NEUTRALIZE W/DILUTE ACID. USE VACUUM TRUCK TO PICK UP NEUT MATL FOR DISPOS AFTER ALL VIS TRACES REMOVED, FLUSH AREA W/WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions: DO NOT GET IN EYES, ON SKIN, OR CLOTHING. AVOID BREATHING MIST. DO NOT TAKE INTERNALLY. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: FOR MIST CONC > TLV-NIOSH/MSHA-APPRD MECH FILTER TYPE /IAW 29CFR 1910.134
Ventilation: LOCAL EXHAUST
Protective Gloves: PVC OR RUBBER
Eye Protection: CHEM SAFETY GOGGLES W/FACE SHIELD
Other Protective Equipment: RUBBER BOOTS W/SAFETY TOES; RUBBER APRON, PVC CLOTHING, PLASTIC HARD HAT; EYE WASH

FOUNTAIN & SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:B.P. Text:288F,142C

Melt/Freeze Pt:M.P/F.P Text:45.0F,7.2C

Vapor Pres:< 1

Spec Gravity:1.530

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR TO SLIGHTLY TURBID, ODORLESS LIQUID.

Percent Volatiles by Volume:50

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ORGANIC MATLS & CONC ACI

DS,METALS LIKE MAGNESIUM,ZINC,

TIN,CHROMIUM,BRASS,BRONZE

Hazardous Decomposition Products:REACTION W/FOOD SUGARS MAY FORM CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:USE APPROVED HAZ WASTE FACILITY. USE CARE TO PREVENT ENVIR CONTAM. COMPLY W/ALL FED,STATE & LOCAL LAWS & REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

o

f Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.