

EASTMAN KODAK COMPANY -- 100 1247 EKTAPRINT K DEVELOPER -- 6850-01-055-9332  
===== Product Identification =====

Product ID:100 1247 EKTAPRINT K DEVELOPER  
MSDS Date:10/16/1996  
FSC:6850  
NIIN:01-055-9332  
MSDS Number: BGJLG  
=== Responsible Party ===  
Company Name:EASTMAN KODAK COMPANY  
Address:343 STATE STREET  
City:ROCHESTER  
State:NY  
ZIP:14650  
Country:US  
Info Phone Num:716-477-3194 MSDS :800- 242-2424

Em  
ergency Phone Num:716-722-5151  
CAGE:19139

=== Contractor Identification ===  
Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS  
Address:343 STATE ST  
Box:City:ROCHESTER  
State:NY  
ZIP:14650-1115  
Country:US  
Phone:716-722-5151/(800) 242-2424

CAGE:19139  
Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES  
Address:800 LEE RD  
Box:City:ROCHESTER  
State:NY  
ZIP:14650-3129  
Country:US  
Phone:800-828-6203  
CAGE:5K871

===== Composition/Information on Ingredients =====

Ingr

ed Name:IRON  
CAS:7439-89-6  
RTECS #:NO4565500  
Fraction by Wt: 95-99%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:STYRENE METHYLMETHACRYLATES COPOLYMER  
CAS:63149-52-0  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9596

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN  
Routes of Entry: Inh  
Absorption:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD  
FOR RECOMMENDED HANDLING. MAY CAUSE TRANSIENT EYE IRRITATION. LOW  
SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW  
INGESTION HAZARD. OVEREXPOSURE TO CARBON BLACK DUST MAY RESULT IN  
IRRITATION OF THE RESPIRATORY TRACT AND BENIGN DEPOSITION OF CARBON  
BLACK IN LUNGS  
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT  
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT  
CARCINOGENS.  
Effects of Overexposure:EYE IRRITATION, RESPIRATORY TRACT IRRITATION,  
BENIGN DEPOSITION OF CARBON BLACK IN LUNGS.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL  
ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY

EDIATELY WITH

WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:COMBUSTIBLESOLID

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedur

es:FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS

DECOMPOSITION PRODUCTS. WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST- AIR MIXTURES.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT USE A VACUUM CLEANER TO CLEAN UP SPILLS OF POWDERED TONERS. THE VERY FINE PARTICLES CAN CAUSE A FIRE OR EXPLOSION. SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CARTON.

AVOID GENERATION OF DUS T. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING DUST. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER CLOSED. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. MINIMIZE DUST GENERATION.

Other Precautions:MINIMIZE DUST ACCUMULATION. REFER TO NFPA PAMPHLET NO. 654, "PREVENTION OF FIRE AND DUST EXPLOSIONS IN THECHEMICAL, DYE, PHARMACEUTICAL, AND PLASTICS INDUSTRIES."

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT

SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Decomp Temp:Decomp Text:NOT GIVEN

Vapor Pres:NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Spec Gravity:2.3

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK POWDER, SLIGHT ODOR

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF IRON

===== Disposal Considerations =====

Waste Disposal Methods:CAN BE INCINERATED WHEN IN COMPLIANCE WITH LOCAL REGULATIONS. CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY. DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner

whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.