

EASTMAN KODAK COMPANY -- 162 0509,RP X-OMAT DEVL/REPL,PT B(POST 85) --
6525-01-061-1694

===== Product Identification =====

Product ID:162 0509,RP X-OMAT DEVL/REPL,PT B(POST 85)

MSDS Date:11/05/1985

FSC:6525

NIIN:01-061-1694

MSDS Number: BGJTB

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-515

1

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 77.5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:50

00 LBS

Ingred Name:1-PHENYL-3-PYROZOLIDINONE (10-15%)

CAS:92-43-3

RTECS #:UQ8750000

Fraction by Wt: 12.5%

Ingred Name:WATER (5-10%)

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 07.5%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:CAUSES SEVERE SKIN & EYES BURNS;
VAPORS CAUSE IRRITATION.

Effects of Overexposure:INH:VAP MAY

CAUSE IRRITN;EYES:LIQ CONTCT MAY

CAUSE BURNS;SKIN:LIQ CAUSES IRRIT/ALLERGIC REACTION.

Medical Cond Aggravated by Exposure:NOT NOTED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:GET MED ATTN IF IRRITATION OF EYES/SKIN PERSISTS.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:123F/51C

Extinguishing Media:WATER SPRAY,DRY CHEMICALS,CO*2

Fire Fighting Procedures:WEAR SELF-CONTAINED BREAT

HING APPARATUS AND

PROTECTIVE CLOTHING TO PREVENT SKIN & EYES CONTACT.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGN SOURCES.STOP LEAK W/O RISK.WEAR

PROTECTV EQUIPMNT;NEUTRALIZE SM SPILL W/SPDIUM BICARBONATE.FLUSH TO

SEWER IAW FED,STATE & LOCAL REGS;LG SPILL:DIKE FAR AHEAD

W/COMMERCIAL ABSORBENT FOR LATER DISPOSAL OR PUMP LIQ TO COVERED
DRUMS.

===== Handling and Sto

rage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:NONE KNOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR SHOULD
BE WORN IF NEEDED.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE USED.LOCAL EXHAUST
VENTILATION OR AN ENCLOSED HANDLING S
YSTEM MAY BE NEEDED.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:SAFETY GL W/SIDESHIELDS OR FACE SHIELD

Other Protective Equipment:IMPERVIOUS CLOTHING,EYE WASH & SAFETY SHOWER

Work Hygienic Practices:WASH THOROUGHLY BEFORE DRINKING/SMOKING.

Supplemental Safety and Health

THIS IS PART B OF A 3 PARTS PRODUCT.ALL PARTS NEEDED TO MAKE 200 GAL
WORKING SOLUTION;THIS FORMULATION OF CAT #162 0509 REPLACES THE OLD
CAT #122 6240/141 8151 FORMULATION;OLD FORMULA ENTRY SEE PNI-A; FOR
PART

A,SEE NSN 6525-01-061-1693 ANDFOR PART C,SEE NSN
6525-01-061-4366.

===== Physical/Chemical Properties =====

HCC:C2

Vapor Pres:13.4MM@20C

Vapor Density:1.66

Spec Gravity:1.085

pH: