

DOW CORNING CORP -- Q3-6061 PRIMER -- 8040-01-064-1946

=====
Product Identification
=====

Product ID:Q3-6061 PRIMER

MSDS Date:01/01/1985

FSC:8040

NIIN:01-064-1946

MSDS Number: BGJXY

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Co

ntractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: >90%

OSHA PEL:100 P

PM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYSILOXANE
RTECS #:TR0460000

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE SLIGHT ANESTHESIA,HEADACHE ETC.MAY IRRITATE SKIN & EYES.

=====
First Aid Measures
=====

First Aid:INHAL-MOVE TO FRESH AIR OBTAIN MEDICAL ATTENTION.SKIN & EYES-FLUSH W/WATER.

=====
Fire Fighting Measure

S =====

Flash Point:60 F CC
Lower Limits:1.4
Upper Limits:7.5
Extinguishing Media:CARBON DIOXIDE OR FOAM
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:MOP UP,WIPE OR SOAK UP WITH ABSORBENT MATERIAL USING PROPER PROTECTIVE EQUIPMENT.AVOID SPARKS & KEEP FROM HEAT.

=====
Handling and Storage
=====

Handling and Storage Precaution
s:SAME AS FOR ANY FLAMMABLE PRODUCT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:ORGANIC VAPOR TYPE
Ventilation:GENERAL MACHANICAL RECOMMENDED
Protective Gloves:RUBBER OR PLAST
Eye Protection:SAFETY GLASSES
Other Protective Equipment:AS REQUIRED
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:260 F
Vapor Pres:40
Vapor Density:>1
Spec Gravity:0.8
Evaporation Rate & amp

; Reference:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL

Hazardous Decomposition Products:SiO₂,CO₂,TRACES OF INCOMPLETELY
BURNED CARBON PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN APPROVED DOT CONTAINER FOR SHIPMENT TO
DISPOSAL AREA.CAN BE BURNED IN ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by
the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.