

FURANE PRODUCTS; M & T CHEMICALS, INC. -- URALANE HARDENER 5738B -- 8040-01-081-3370
===== Product Identification =====

Product ID:URALANE HARDENER 5738B
MSDS Date:01/01/1985
FSC:8040
NIIN:01-081-3370
MSDS Number: BGKWP
=== Responsible Party ===
Company Name:FURANE PRODUCTS; M & T CHEMICALS, INC.
Emergency Phone Num:213-247-6210
CAGE:GO766
=== Contractor Identification ===
Company Name:CIBA SPECI
ALTY CHEMICALS CORP, N. A. / PERFORMANCE
POLYMERS
Address:5121 SAN FERNANDO RD WEST
Box:City:LOS ANGELES
State:CA
ZIP:90039-1011
Country:US
Phone:818-247-6210/800-873-1138
CAGE:99384
CAGE:GO766

===== Composition/Information on Ingredients =====

Ingred Name:POLY AROMATIC AMINE;TLV UNKNOWN:ALBINO RAT LD50:2500
MG/UG(SEE BELOW)
Fraction by Wt: 100%

===== Hazards Identification =====

Effects of Overexposure:NO APPARENT PROBLEMS,PER MFG:
USE STANDARD
CHEMICAL HANDLING/SAFETY PRACTICES.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES,BREATHING DIFFICULTY, OR OTHER
SYMPTONS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>325F >162C(COC)
Extinguishing Media:WAER OR ANY COMMERCIAL UNIT
Fire Fi

ghting Procedures:WEAR SELF-CNTND BRTHG APP:H*2O SPRAY TO COOL
CONTR.

Unusual Fire/Explosion Hazard:MATL MAY/MAY NOT BURN. CONTAINER MAY
EXPLODE IN HEAT OF FIRE.FIRE MAY YIELD TOXIC GASES.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION
SOURCES. STOP LEAK. H*2O SPRAY COOL CONT/DIVERT SPILL FROM
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W/COMMERCIAL
ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPIL
L:DI KE W COMMERCIAL
ABSORBENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE
RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.
KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:MAINTAIN STRICT HYGIENE,AVOID PHYSICAL CONTACT,REMOVE
&WASH CONTAMINATED CLOTHING. MFG SUGGESTS USE OF PROTECTIVE SKIN
CREAMS. EXHAUST CURING OVENS TO OPEN AIR. AVOID
TEMPERATURE
EXTREMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.

Ventilation:MECHANICAL (GENERAL/LOCAL EXHAUST)

Protective Gloves:PV/RUBBER

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.

Supplemental Safety and Health

PART B OF 2 PART PRODUCT. THIS PART IS HARDENER. SEE P/N A FOR PART A
(RESIN) A

LBIN O RABBITS: EYE 17/110;SKIN 0.1/8.0(PRACTICALLY
NON-IRRITATING. KEY1:N1

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Spec Gravity:1.24

Solubility in Water:SLIGHT

Appearance and Odor:DARK AMBER LIQUID; AMINE ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACIDS AND PEROXIDES

Stability Condition to Avoid:HEAT, IGNITION SOURCES

Hazardous Decomposition Products:NONE NOTED, BUT EXPECT CO,CO*2, H*2O.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.
HANDLE AND DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE AND LOCAL REGULATIONS. MFG SUGGESTS
BURY IN APPROVED LANDFILL, OR REA CT W RESIN & DISPOSE AS SOLID
WASTE;WASH RESIDUE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.