

PRODUCTS RESEARCH & CHEMICAL CORPORATION -- PR-1201-RLS -- 8030-01-084-6957

=====
Product Identification
=====

Product ID:PR-1201-RLS

MSDS Date:01/01/1987

FSC:8030

NIIN:01-084-6957

Kit Part:Y

MSDS Number: BGKZX

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2

060

Emergency Phone Num:818-240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

=====
Composition/Information on Ingredients
=====

Ingred Name:LEA

D PEROXIDE (LEAD DIOXIDE), (OSHA PEL FROM 29CFR
1910.1025)

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 7.0%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:BASE COMPD MAY BE SKIN IRRITNT.CATALYST
CONTAINS LEAD
WHICH MAY BE ABSORBED THROUGH SKIN.

=====
===== First Aid Measures =====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP & WATER.EYES:WASH OUT
THOROUGHLY WITH LARGE AMOUNTS OF WATER.SEE A
PHYSICIAN.INGESTION:INDUCE VOMITING.INHALATION:REMOVE TO FRESH
AIR.GIVE CPR/OXYGEN IF NECESSARY.

=====
===== Fire Fighting Measures =====

Flash Point:92F/33.3C PMCC

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,DRY CHEMICAL,CARBO
N DIOXIDE

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APPARATUS WHEN FIGHTING
FIRES.

Unusual Fire/Explosion Hazard:EMISSION OF TOXIC VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK.ELIMINATE IGNITION SOURCES.KEEP
UNPROTECTED PERSONS FROM HAZARD AREA.ABSORB EXCESS WITH RAGS,PAPER
TOWELS.CLEAN AREA WITH TOLUENE OR XYLENE.PLACE IN CLOSED
CONTAINERS.

=====
===== Handling and Storage =====

=

Handling and Storage Precautions:KEEP IN CLOSED CONTAINERS AT ROOM TEMPERATURE.AVOID ACCELERATOR SPILLAGE.AVOID FIRE HAZARDS.PROTECT FROM PHYSICAL DAMAGE.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED RESPIRATOR RECOMMENDED IN CONFINED AREAS.

Ventilation:MECHANICAL/LOCAL EXHAUST ADEQUATE TO MINIMIZE SOLVENT VAPORS

Protective Gloves:POLYETHYLENE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:USE PROTECTIVE HAND CREAM

Supplemental Safety and Health

PERCENT VOLATILE BY VOLUME IS 6% MAXIMUM

=====
===== Physical/Chemical Properties =====

HCC:F3

Vapor Pres:UNK

Vapor Density:UNK

Spec Gravity:1.62

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PINKISH BROWN,THICK LIQUID,SLIGHT TOLUENE ODOR

Percent Volatiles by Volume:6

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:Y

ES

DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT SOURCES

Hazardous Decomposition Products:OXIDES OF SULFUR;HYDROGEN SULFIDE;FORMIC ACID

=====
===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN CLOSED CONTAINERS AND DISPOSE IN ACCORDANCE WITH LOCAL,FEDERAL,AND STATE REGULATIONS.DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formul

ated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.