

NORRIS PAINT CO -- DREAMHOUSE EXTERIOR LATEX PAINT -- 8010-01-091-0752

=====
Product Identification
=====

Product ID:DREAMHOUSE EXTERIOR LATEX PAINT

MSDS Date:01/01/1987

FSC:8010

NIIN:01-091-0752

MSDS Number: BGLMD

=== Responsible Party ===

Company Name:NORRIS PAINT CO/SALEM, OR 97303

Emergency Phone Num:(503) 364-2277

CAGE:MO898

=== Contractor Identification ===

Company Name:NORRIS PAINT CO/SALEM

, OR 97303

CAGE:MO898

Company Name:PERIPHERAL COMPUTER SYSTEMS INC

Address:179 LEGRAND AVE

Box:161

City:NORTHVALE

State:NJ

ZIP:07647-2404

Country:US

CAGE:33418

=====
Composition/Information on Ingredients
=====

Ingred Name:PHENYLMERCURIC ACETATE (SARA III)

CAS:62-38-4

RTECS #:OV6475000

Fraction by Wt: 0.1%

OSHA PEL:0.1 MG HG/M3;CEIL;S

ACGIH TLV:0.01 MG HG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2%
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Effects of Overexposure:SKIN/EYES: IRRITATION & DERMATITIS. INGESTION:
CAN CAUSE NAUSEA, VOMITING, DIARRHEA.

=====
First Aid Measures
=====

First Aid:INGESTION: DON'T INDUCE VOMITING: CALL PHYSICIAN. SKIN:
REMOVE CONTAMINATED CLOTHING. SKIN: WASH W/SOAP & WATER. EYES:
FLUSH
WITH CLEAR WATER UNTIL IRRITATION SUBSIDES. CONSULT
PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:NON-FLAMMABLE

=====
Accidental Release Measures
=====

Spill Release Procedures:ISOLATE THE AREA, RECOVER FREE LIQUID WITH AN
ABSORBENT (SAND, EARTH, SAWDUST, ETC.)KEEP OUT OF SEWERS BY DIKING,
IMPOUNDING.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP
CONTAINERS CLOSED WHEN NOT IN
USE.
Other Precautions:KEEP FROM FREEZING.

=====
Exposure Controls/Personal Protection
=====

Protective Gloves:AS NEEDED
Eye Protection:SPLASH GOGGLES
Supplemental Safety and Health
MSDS DATE: 6/5/87. WT PER GAL: 11

=====
Physical/Chemical Properties
=====

HCC:N1
Boiling Pt:B.P. Text:108F
Vapor Pres:ML
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60%

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
VINYL ACETATE MONOMER; ACRYLIC MONOMER

===== Disposal Considerations =====

Waste Disposal Methods: ASSURE CONFORMITY WITH APPLICABLE DISPOSAL
REGULATIONS FOR BOTH SPILLED PRODUCT AND ABSORBED MATERIAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense.

The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.