

DU PONT E I DE NEMOURS & CO INC -- STADIS 450 CONDUCTIVITY IMPROVER -- 6850-01-097-2060  
===== Product Identification =====

Product ID:STADIS 450 CONDUCTIVITY IMPROVER

MSDS Date:11/19/1994

FSC:6850

NIIN:01-097-2060

MSDS Number: BGLQW

=== Responsible Party ===

Company Name:DU PONT E I DE NEMOURS & CO INC

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE

ZIP:19898

Country:US

Info Phone Nu

m:800-441-7515/MSDS 302-992-3511

Emergency Phone Num:800-441-3637/800-424-9300(CHEMTREC)

Preparer's Name:D.C.ZIMMERMAN

CAGE:18873

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

=====

Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 50-65%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA)

CAS:64742-94-5

RTECS #:WF3100000

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction b

y Wt: 0-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NEW JERSEY TRADE SECRET #0085020100L-5457P

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DODECYLBENZENESULFONIC ACID (SARA III)

CAS:27176-87-0

RTECS #:DB6600000

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NEW JERSEY TRADE SECRET REGISTRY NO. 00850201001-5037 P

Fraction by Wt: 1-10%

Other REC L

imits:NONE RECOMMENDED

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 1(N-BUTYL ACETATE = 1)

Solubility in Water:SLIGHT

Appearance and Odor:AMBER COLOR LIQUID,TOLUENE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OPEN FLAMES

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE,  
SULFUR DIOXIDE

Condi

tions to Avoid Polymerization:UNK

===== Disposal Considerations =====

Waste Disposal Methods:DESTROY BY BURNING/LIQUID INCINERATION IAW LOCAL  
REGULATIONS PROD ABSORBED ON ABSORBENT MATERIAL MAY BE DEPOSITED IN  
A LANDFILL IAW LOCAL,STATE & FED REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever

, expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.