View NSN Online: https://aerobasegroup.de/nsn/9150-01-099-2845

ZURN O F CO -- ZURN E.P. LUBE #80 -- 9150-01-099-2845

Product ID:ZURN E.P. LUBE #80

MSDS Date:01/01/1987

FSC:9150

NIIN:01-099-2845

MSDS Number: BGLSN === Responsible Party === Company Name: ZURN O F CO Address: 2736 N BROAD ST

Box:6779

City:PHILADELPHIA

State:PA

ZIP:19132-2721 Country:US

Emergency Phone Num:215-229-5268

CAGE:55004

=== Contractor Identification === Company Name:ZURN O F CO Address:2736 N BROAD ST

Box:6779

City:PHILADELPHIA

State:PA

ZIP:19132-2721 Country:US

Phone:215-229-5268

CAGE:55004

======= Composition/Information on Ingredients ========

Ingred Name: PETROLEUM HYDROCARBON

Fraction by Wt: >98%

ACGIH TLV:5MG/CUM(OILMIST

Ingred Name: ADDITIVES (SULPHUR+PHOSPHORUS)

Fraction by Wt: 275F,>135C

Autoignition Temp: Autoignition Temp Text: UNKNOW

Lower Limits: 0.9 Upper Limits: 7.0

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOA

M, OR DRY

CHEMICAL. WATER MAY BE LESS EFFECTIVE AND CAUSE FROTHING.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS. DENSE SMOKE MAY BE EXPECTED.

======== Accidental Release Measures ============

Spill Release P

rocedures:WEAR PROTECTIVE EQUIPMENT, ELIMINATE SOURCES
OF IGNITION, AND VENTILATE AREA AS REQUIRED. RECOVER FREE LIQUID.
ABSORB SMALL SPILL WITH INERT MATERIAL. PLACE WASTE IN DOT APPROVED
CONTAINER FOR DISPOSA L. KEEP FROM SEWERS AND WATERWAYS.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM PHYS

ICAL DAMAGE.

Other Precautions: AVOID BREATHING OF MIST. MINIMIZE PERIODS OF EXPOSURE TO HIGH TEMPERATURE. AVOID WATER CONTAMINATION.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation: MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves: RUBBER GLOVES OR OTHER OIL RESISTANT.

Eve Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

USE AIR-SUPPLIED RESPIRATORY EQUIPMENT IF EXPOSED TO HOT FUMES.

====

======= Physical/Chemical Properties =========
HCC:V6 Boiling Pt:B.P. Text:>500F,>260C Vapor Pres:NEGLIGIBLE Vapor Density:>5 AIR=1 Spec Gravity:0.877 Viscosity:18.6 CST @40C Evaporation Rate & Description Rate &
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH TE MPERATURES, SPARKS, AND OPEN FLAMES Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE. ===================================
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, exp ressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.