View NSN Online: https://aerobasegroup.de/nsn/6810-01-099-3435

ASHLAND CHEMICAL CO. DIVISION OF ASHLAND OIL INC. -- TETRACHLOROETHYLENE 6810-01-099-3435

============= Product Identification ==================

Product ID:TETRACHLOROETHYLENE

MSDS Date:05/31/1989

FSC:6810

NIIN:01-099-3435

MSDS Number: BGLSS === Responsible Party ===

Company Name: ASHLAND CHEMICAL CO. DIVISION OF ASHLAND OIL INC.

Box:2219

City:COLUMBUS

State:OH ZIP:43216 Country:US

Info Phone Num:614-790-3333 OR 80

0-ASH-LAND

Emergency Phone Num:606-324-1133 OR 800-274-5263

CAGE:5A188

=== Contractor Identification ===

Company Name: ASHLAND CHEMICAL CO

Address:5200 PAUL BLAZEL MEMORIAL PARKWAY

Box:City:DUBLIN

State:OH ZIP:43017 Country:US

Phone:614-889-4505

CAGE:5A188

======= Composition/Information on Ingredients ========

Ingred Name: PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III) *

CAS:127-18-4

RTECS #:KX3850000 Fraction by Wt: 100%

Other REC Limits: NONE SPECIFIED

OSHA PEL:25 PPM *

ACGIH

TLV:50 PPM/200 STEL;9192 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS ========== Hazards Identification =========================== Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES | IARC:YES | OSHA:NO Health Hazards Acute and Chronic:ACUTE-EYE:CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS. EXCESSIVE INHALATION: CAN CAUSE IRRITATION, CNS E FFECT S INCLUDING DIZZINESS, HEADACHE, FATIGUE, UNCONSCIOUSNESS/DEATH. INGESTION: CAN CAUSE GI IRRITATION, VOMITING, DIARRHEA. Explanation of Carcinogenicity: IDENTIFIED AS A CARCINOGEN BY IARC, NTP (PER MSDS). Effects of Overexposure: CHRONIC OVEREXPOSURE: MAY CAUSE LIVER ABNORMALITIES, KIDNEY DAMAGE, SPLEEN DAMAGE, BRAIN DAMAGE. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:GET MEDICAL ATTENT ION IF NEEDED.EYE:FLUSH W/ WATER 15 MIN, HOLD LIDS OPEN. SKIN: WASH WITH SOAP & WATER. INHALED: REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NECESSARY.KEEP PERSON WARM & QUIET.DON'T GIVE STIMUL ANTS.EPINEPHRINE/EPHEDRINE MAY ADVERSELY AFFECT THE HEART WITH FATAL RESULTS.IF SWALLOWED:DON'T INDUCE VOMITING.IF CONSCIOUS, IMMEDIATELY DRINK TWO GLASSES OF WATER. Flash Point: NOT RELEVANT Extinguishing Media: NON FLAMMABLE. US E WATER FOG, CARBON DIOXIDE/DRY CHEMICAL FOR SURROUNDING FIRE.USE WATER TO COOL FIRE-EXPOSED CONTAINERS. Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WITH A

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

======== Accidental Release Measures =========

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS.ABSORB SMALL SPILLS ON PAPER,VERMICULITE,.STOP LEAK FOR LARGE SPILLS.DIKE AREA.PUMP LIQUID TO SALVAGE TANK.TAKE UP THE REST BY SAND/CLAY AND SHOVEL TO A CONTAINER.

Neutralizing Agent: NONE GIVEN

========== Handling and Storage ===============

Handling and Storage Precautions:STORE CONTAINERS TIGHTLY CLOSED IN A COOL, WELL VENTILATED PLACE,AWAY FROM HEAT & FLAMES.EMPTY CONTAINER MAY CONTAIN HAZARDOU

S RESIDUES.

Other Precautions: OBSERVE ALL PRECAUTIONS GIVEN IN THE DATA SHEET.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:IF WORKPLACE EXPOSURE LIMIT OF PRODUCT EXCEEDS THE TLV, A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED. Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION.

Protective Gloves: POLYVINYL ALCOHOL

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: EYEWASH STATION AND SAFETY SHOWER.

IM

PERVIOUS CLOTHING AND BOOTS

Work Hygienic Practices: DO NOT INHALE VAPORS. WASH HANDS BEFORE EATING AND DRINKING.

Supplemental Safety and Health

NONE

======== Physical/Chemical Properties ==========

HCC:T4

Boiling Pt:B.P. Text:250F,121C

Vapor Pres:13 Vapor Density:6.7

Spec Gravity: 1.618 - 1.622

Evaporation Rate & Department of the Evaporation Rate & Department & Departmen

Percent Volatiles by Volume:100

======= Stability and Rea

Stability Indicator/Materials to Avoid:YES
NOT RELEVANT
Stability Condition to Avoid:HIGH TEMPERATURES AND FLAMES
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS: CARBON
DIOXIDE AND CARBON MONOXIDE, HYDROGEN CHLORIDE, PHOSGENE, VARIOUS

======= Disposal Considerations ===========

Waste Disposal Methods: CONSULT FEDERAL, STATE AND LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES.

Disclaimer (provi

ctivity Data ========

HYDROCARBONS, ETC..

ded with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.