

TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC -- TRITON I ACTIVATOR SOLUTION --
6850-01-106-7671

===== Product Identification =====

Product ID:TRITON I ACTIVATOR SOLUTION

MSDS Date:01/01/1987

FSC:6850

NIIN:01-106-7671

MSDS Number: BGMDJ

=== Responsible Party ===

Company Name:TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC

Address:331 N OAK ST

Box:398

City:OWEN

State:WI

ZIP:54460

Country:US

Emergency Pho

ne Num:201-647-1040

CAGE:MO933

=== Contractor Identification ===

Company Name:TELEDYNE INC

Address:150 MT BETHEL ROAD

Box:City:WARREN

State:NJ

ZIP:07060-5147

Country:US

CAGE:23428

Company Name:TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC

Address:331 N OAK ST

Box:398

City:OWEN

State:WI

ZIP:54460

Country:US

CAGE:MO933

===== Composition/Information on Ingredients =====

Ingred Name:ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: UNK

OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3 PP

M/6 STEL; 9192

Ingred Name:DIPROPYLENE GLYCOL,1,1'-OXYDI-2-PROPANOL

CAS:110-98-5

RTECS #:UB8785000

Fraction by Wt: UNK

=====
===== Hazards Identification =====
=====

Health Hazards Acute and Chronic:CONTACT WITH EYES CAUSES BURNS. SKIN CONTACT MAY CAUSE IRRITATION. BREATHING OF VAPORS MAY CAUSE COUGHING AND DISCOMFORT IN NOSE,THROAT AND CHEST.

Medical Cond Aggravated by Exposure:MANUFACTURER DID NOT SPECIFY.

=====
===== First Aid Measures =====
=====

First Aid:IMMEDIATELY FLUSH SKIN & EYE CONTACT W/PLENTY OF WATER FOR AT LEAST 15 MINUTES.GET MEDICAL CARE FOR EYES.

=====
===== Fire Fighting Measures =====
=====

Flash Point:200F/280F COC

Lower Limits:5/1

Upper Limits:17/9

Extinguishing Media:CO*2 OR DRY CHEMICAL

Fire Fighting Procedures:DILUTION OF BURNING LIQUID WITH WATER WILL REDUCE FLAME INT.

Unusual Fire/Explosion Hazard:WIL BURN;MAY EXPLODE;RUN OFF MAY POLLUTE/CREATE EXPLOSV FIRE HAZARD

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:FLUSH WITH LARGE VOLUMES OF WATER.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:WARNING:STRONG ALKALINE

SOLUTION.HARMFUL IF SWALLOWED,AVOID CONTACT WITH EYES,SKIN,OR CLOTHING.IN CASE OF CONTACT WITH EYES OR SKIN FLUSH W/H*20-15MIN

Other Precautions:FOR EYES GET MEDICAL ATTENTION.

=====
===== Exposure Controls/Personal Protection =

=====

Respiratory Protection:NONE REQD.
Ventilation:LOCAL EXHAUST & MECHANICAL IS RECOMMENDED.
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Other Protective Equipment:EYE BATH & SAFETY SHOWER
Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE
EATING,SMOKING,USING SANITARY FACILITIES.
Supplemental Safety and Health
UPDATE PER UNDATED MSDS OSHA FORM 20 RECEIVED 8JAN88.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:339F/451
Vapor
Pres: