

FISKE BROTHERS REFINING CO -- LUBRIPLATE 630-AA -- 9150-01-109-8726

=====
Product Identification
=====

Product ID:LUBRIPLATE 630-AA

MSDS Date:01/01/1987

FSC:9150

NIIN:01-109-8726

MSDS Number: BGMGJ

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Emergency Phone Num:201-589-9150

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD S

T

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:LITHIUM SOAP

ACGIH TLV:NOT KNOWN

Ingred Name:ADDITIV

ES- TYPE NOT SPECIFIED
ACGIH TLV:NOT KNOWN

===== Hazards Identification =====

Effects of Overexposure:PROLONGED/REPEATED SKIN CONTACT MAY CAUSE MILD IRRITATION.

===== First Aid Measures =====

First Aid:SKIN: WASH THOROUGHLY W/SOAP & WARM WATER; EYES: FLUSH W/CLEAR WATER FOR 15 MIN. OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:400F/204C COC

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL, CO*2, WATER FOG OR WATER SPRAY.

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:DONOT MIX OR STORE W/STRONG OXIDANTS LIKE LID. CHLORINE/CONCENT.O*2; //AVOID BRTHG VAPOR/FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAP UP GREASE;WASH RESIDUE W/APPROVED PET

ROLEUM SOLVENT.KEEP PETROLEUM PRODUCTS OUT OF SEWERS & WATER COURSES.ADIVSE APPROPRIATE AUTHOITIES IF PRODUCT MAY OR HAS ENTERED SUCH ENVIRONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOED WHEN NOT IN USE.

DONOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAME OR STRONG OXIDANTS.

Other Precautions:AVOID BREATHING OIL MISTS.REMOVE OIL SOAKED CLOTHING & LAUNDER BEFORE RE-USE.

===== Exposure Controls/Pe

Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED
Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES & VAPORS
Protective Gloves:OIL RESISTANT
Eye Protection:CHEMICALGOGGLES/SAFETY
Other Protective Equipment:USE OIL RESISTANT APRON IF NEEDED
Supplemental Safety and Health
MSDS UNDATED

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>750F/>399C
Vapor Pres:14.
Spec Gravity:0.95
Evaporation Rate & Reference:(BU-AC =1) < 0
.01
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT TAN GREASE W/MINERAL OIL ODOR
Percent Volatiles by Volume:NEGL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS:LIQUID CHLORINE, CONCENTRATED OXYGEN
Stability Condition to Avoid:MFR CITES NONE+SITUATIONS WHERE
HI-TEMPS/OXIDIZERS PRESENT
Hazardous Decomposition Products:MFR CITED NONE; CO*2, CO, OXIDES OF
ADDITIVES
Conditions to Avoid Polymerization:
WILL NOT POLYMERIZE

===== Disposal Considerations =====

Waste Disposal Methods:ASSURE CONFOMITY WITH APPLIABLE DISPOSAL
REGULATIONS.DISPOSE OF ABSORBED MATERIAL AT AN APPROVED WASTE
DISPOSAL FACILITY OR SITE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this i

nformation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.