

EASTMAN KODAK CO. -- 180 3998,MICROFILM CLEARING BATH & REPL -- 6750-01-129-0866

===== Product Identification =====

Product ID:180 3998,MICROFILM CLEARING BATH & REPL

MSDS Date:08/18/1982

FSC:6750

NIIN:01-129-0866

MSDS Number: BGNDN

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Ph

one Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM SULFITE

CAS:10117-38-1

Fraction by Wt: 15-20%

Other REC Limits:NONE ESTABLISHED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 75-80%

Other RE

C Limits:NONE ESTABLISHED

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:MSDS FM MFR STATES THAT EFFECTS OF OVEREXPOSURE
ARE OF LOW HAZARD TO HEALTH.

===== First Aid Measures =====

First Aid:PER MFR MSDS,"NONE INDICATED.";HOWEVER,FLUSH W/LG AMT OF
WATER IN CASE OF SKIN/EYE CONTACT.GET MED ATTN IF
NEEDED OR
SYMPTOMS OCCUR.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:CO*2,FOAM,DRY CHEM

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS,PROVIDE
VENTILATION/SAFETY EQUIPMENT IF NECESSARY.DIKE LG SPILL & PUMP INTO
COVERED CONTNRS;ABSORB SM SPILL W/ABSORBING MATL & PLACE IN SAME
CONTNR;MFR SUGGESTS FLUSH DOWN TO SEWER W/LG AMT OF H*2O IAW

EXISTINGREGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL
DAMAGE.
Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE &
WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF
PRODUCT:8.4

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQD IN NORMAL CONDIT

IONS.
Ventilation:MECHANICAL(GEN) IF NEEDED
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES
Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES.
Supplemental Safety and Health
MSDS FM MFR DATED:08/18/82

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>212F/>100C
Vapor Pres:17
Vapor Density:0.6
Spec Gravity:1.22
pH:8.4
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR,ODORLESS LIQUID
Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
PER MFR,MINERAL ACIDS
Hazardous Decomposition Products:PER MFR,SULFURDIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING
DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL,STATE & LOCAL
REGULATIONS;MFR RECOMMENDS TO FLUSH DOWN TO SEWER W COPIOUS AMT
H*2O.STATE & LOCAL EFFLUENT LAWS TAKE PRE CEDENCE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.