

RAYCHEM CORPORATION -- S-1125 EPOXY ADHESIVE, PART B, EPOXY RESIN -- 8040-01-147-9957

=====
Product Identification
=====

Product ID:S-1125 EPOXY ADHESIVE, PART B, EPOXY RESIN

MSDS Date:01/01/1987

FSC:8040

NIIN:01-147-9957

MSDS Number: BGNXT

=== Responsible Party ===

Company Name:RAYCHEM CORPORATION

Emergency Phone Num:(415) 361-3333/4360

CAGE:06099

=== Contractor Identification ===

Company Name:R

AYCHEM CORP

Address:300 CONSTITUTION DRIVE

Box:City:MENLO PARK

State:CA

ZIP:94025-1164

Country:US

Phone:415-361-4907

CAGE:06090

Company Name:RAYCHEM CORPORATION

Address:300 CONSTITUTION DRIVE

City:MENLO PARK

State:CA

ZIP:94025

Phone:(415)361-3333

CAGE:06099

=====
Composition/Information on Ingredients
=====

Ingred Name:EPICHLOROHYDRIN/BISPHENOL A TYPE EPOXY RESIN,MODIFIED.

Ingred Name:UNIDENTIFIED COMPONENT

=====
Hazards Identification
=====

=

Effects of Overexposure:SKIN/EYES:IRRIT.MAY DAMAGE EYE.MAY SENSITIZE
SKIN ON RPTD CONTCT;INHAL/INGEST:IRRIT RESP SYS,DIZZ.

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighting Measures
=====

Flash

Point:NONE

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL
CONTR.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PROTECTIVE EQUIP DURING CLEAN
UP. COVER SPILLED MATL WITH ABSORBENT & SHOVEL INTO CONTAINER.
CLEAN UP RESIDUE WITH SOAP AND WATER. DO NOT FLUSH TO SEWER.

===== Handling and
Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED

Other Precautions:AVOID SKIN/EYES CONTACT.WASH HANDS THOROUGHLY AFTER
USE/HANDLING.AVOID BREATHING LOW LEVEL VAP GIVEN OFF DURING
ASSEMBLY & CURE & DUST FROM GRINDING/SANDING OPERATION.USE IN
ADEQUATE VENTILN.

===== Exposure Controls/Personal Protection =====

Respi
ratory Protection:NONE SHOULD BE NEEDED
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT.
Protective Gloves:RUBBER/PLASTIC
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.
Supplemental Safety and Health
MSDS FROM RAYCHEM CORP EFFECTIVE: MAY 1985;ITEM IS 2 PART
PRODUCT.SUPPLD PREKD IN SEALED MIXING BAG.BOTH PART IN MIXING BAG
ARE SEPARTD BY MEANS OF A CLIPPED ROD;THIS IS PART B,EPOXY
RESIN.KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:1.33
Solubility in Water:SLIGHT
Appearance and Odor:VISCOUS BLACK PASTE WITH SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ACIDS, BASES
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:BURNING PROCESS OXIDES OF CARBON AND
AMMONIA

===== Disposal Considerations =====

Waste Disposal Methods

:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.