View NSN Online: https://aerobasegroup.de/nsn/6850-01-167-5227 VERSATEC INC (REPLACED BY XES INC, VERSATEC PROD.) -- 4405-1GR TYPE H TONER PREMIX --6850-01-167-5227 Product ID:4405-1GR TYPE H TONER PREMIX MSDS Date:01/01/1987 FSC:6850 NIIN:01-167-5227 MSDS Number: BGPNZ === Responsible Party === Company Name: VERSATEC INC (REPLACED BY XES INC, VERSATEC PROD.) Address:2710 WALSH AVE. City:SANTA CLARA State:CA ZIP:95051-0905 Cou ntry:US Info Phone Num:408-985-5810 OR 800-828-6571 Emergency Phone Num:F46-422-2177 (XEROX CORP, NY) CAGE:50804 === Contractor Identification === Company Name: VERSATEC INC (REPLACED BY XES INC, VERSATEC PROD.) Address:2710 WALSH AVE. Box:City:SANTA CLARA State:CA ZIP:95051-0905 Country:US Phone:716-422-2177 (XEROX CORP, NY) CAGE:50804 ======= Composition/Information on Ingredients ========

Ingred Name:ISOPARAFFINIC PETROLEUM SOLVENT(ISOPAR G);CAS

#64742-48-9(PER MFR); TLV 300P

PM PER MFR

Fraction by Wt: >95%

ACGIH TLV:300PPM(PER MFR)

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL

CAS:128-37-0

RTECS #:GO7875000 OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3; 9192

Ingred Name: ROSIN BINDER; PER MFR, CAS #8050-09-7

Ingred Name: MOLYBDATED CARBON BLACK

Ingred Name:ALUMINUM STEARATE; PER MFR,CAS #637-12-7; SEE SUPPLEMENTAL DATA FOR OTHER COMPONENTS.

========== Hazards Identification ===============

Effects of Overexposure: DIRECT INHALATION OF FUMES MAY CAUSE IRRITA

TION TO MUCUS MEMBRANES
======================================
First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST: DO NOT INDUCE VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.
======================================
Flash Point:105F,40C TCC Lower Limits:0.8 Upper Limits:7.0 Extinguishi ng Media:FOAM,DRY CHEMICAL,CO*2,WATER FOG Fire Fighting Procedures:AVOID WATER, IT TENDS TO SPREAD HYDROCARBON SOLVENT FIRES Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ===========
Spill Release Procedures:ELIMINATE IGNITION SOURCE. ABSORB FREE LIQUID WITH SAND,SOIL,ETC. PLACE IN DISPOSAL CONTAINER. FLUSH RESIDUE W/SOAP & WATER. VENTILATE AREA.
======================================
Handling and Storage P recautions:KEEP CONTAINER CLOSED. AVOID HDLG NEAR HEAT, STG LIGHT, SPARKS, OPEN FLAMES, STRG OXIDANTS. Other Precautions:AVOID BRTHG VAPORS. AVOID PROLONGED OR REPEATED SKIN CONTACT.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE Ventilation:NONE Protective Gloves:NONE Eye Protection:OPTIONAL Other Protective Equipment:NEOPRENE OR NITRILE GLOVES FOR PROLONGED/REPEATED SKIN CONT. Supplemental Safety and Health MSDS FM MFR DATED:16JUL8

5;NIOSH6:1002503DA,DISPERSING AGENT;NIOSH7:1002504,NEOCRYL-VINYLTOLUENEBUTYLMETHACRYLATE RESIN;NIOSH8:1000093DY,DYE; WT % & TLVS UNKNOWN;SP GRVTY RANGE:0.75-0.81.
========== Physical/Chemical Properties ==========
HCC:F4 Boiling Pt:B.P. Text:160-177C Vapor Density:5.0 Spec Gravity:0.78 Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK LIQUID,SLIGHT ODOR Percent Volatiles by Volume:>80%
======== Stability and Reactivity Data =========
St ability Indicator/Materials to Avoid:YES STRONG OXIDANTS Stability Condition to Avoid:HEAT, STRONG LIGHT, SPARKS, OPEN FLAMES, STRONG OXIDANTS Hazardous Decomposition Products:NONE

Waste Disposal Methods:DISPOSE OF LIQUID AND ABSORBANT AT AN APPROVED DISPOSAL SITE OR FACILITY I/A/W ALL LOCAL, STATE & FEDERAL REGULATIONS.

======= Disposal Considerations ===========

Disclaimer (provided with this information by the compiling agencies): This information is f ormulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.