

EASTMAN KODAK COMPANY -- 196 3768 HOBBY-PAC COLR SLIDE KIT,STABILIZR --
6750-01-169-1851

===== Product Identification =====

Product ID:196 3768 HOBBY-PAC COLR SLIDE KIT,STABILIZR

MSDS Date:06/01/1985

FSC:6750

NIIN:01-169-1851

Kit Part:Y

MSDS Number: BGPQK

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Nu

m:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:FORMALDEHYDE (SARA III)

CAS:50-00-0

RTECS #:LP8925000

Fraction by Wt: 03.0%

OSHA PEL:SEE 1910.1048

ACGIH TLV:C 0.3 PPM; A2; 9293

EPA Rpt Qty:100

LBS
DOT Rpt Qty:100 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 03.0%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:WATER (90-95)
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 92.5%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation
of Carcinogenicity:FORMALDEHYDE,A MINOR COMPONENT IN
MIXTURE HAS BEEN LISTED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY
IARC.
Effects of Overexposure:INHALATION:LOW HAZARD FOR USUAL INDUSTRL
HANDLING; EYES:VAPOR CAUSES EYE IRRITATION & LACHRYMATION.CONTACT
WITH THE LIQ CAN CAUSE IRRITATION; SKIN:CAUSES SKIN IRRITATION;
INGESTION:NOT KNOWN.

===== First Aid Measures =====

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET ME
D
ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED
HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR BURNS GET
MED ATTN.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING TO PREVENT SKIN AND EYES CONTACT.
Unusual Fire/Explosion Hazard:RUNOFF/SPILL MAY CAUSE POLLUTION,FIRE OR

EXPLOSION HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGN SOURCES.USE PROTECTV EQUIP,PROVIDE VENT.STOP LEAK W/O RISK.DIKE LG SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SMALL SPILL IN CONTNR PENDING DISPOSAL;MFR RECOMMENDS,NEUTRLZ W/SOD BISULFITE TH EN FLUSH TO SEWER W/LG AMT H*2O IAW EXISTG REGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY ,WELL VENTILATED

AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF PRODUCT:7.0

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE USED.LOCAL EXHAUST VENTILATION MAY BE NEEDED TO CONTROL AIR CONTAMINATION TO LIMITS.

Protective Gloves:SHOULD BE WORN.

Eye Protection:GOGGLES OR SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT

Work Hygienic Practices:ROUTINE USE OF NON-ALKALINE(ACID)TYPE OF SKIN CLEANSER WIL HELP MINIMIZE THE POSSIBILITY OF ALLERGIC SKIN REACTION.

Supplemental Safety and Health

KEY1:J5;THE HOBBY-PAC KIT IS 6 PART KIT IT CONSISTS OF COLOR DEVL(PART A&B),COLR BLEACH(PART A&B),FIRST DEVLPR & STABILZR THE OLD KIT HAD 9 PARTS-SEE P

NI A THRU I THIS NSN;CAT #,TRADE NAME & PARTS OF THE KIT WERE CHANGED DURING 1984-85;THIS IS HOBBY-PAC COLOR SLIDE KIT STABILIZER; SOLUTION #3757.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>212F/>100C

Vapor Pres:18MMHG@20C

Vapor Density:1.15

Spec Gravity:1.01

pH:7.0

Evaporation Rate & Reference:0.4 (BU-ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,COLORLESS LIQ,ALDEHYDE ODOR.

Percent Volatiles by Volume:100

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE KNOWN

Stability Condition to Avoid: SOURCE OF IGN

===== Disposal Considerations =====

Waste Disposal Methods: KEEP IN COVERD CONTNRS PENDING DISPOSAL. SHIP
WASTE TO NEUTRALZNG/DISPOSAL AREA IAW DOT/EPA REGS. HANDLE/DISPOSE
OF IAW FED, STATE/LOCAL REGS; MFR SUGGESTS: NEUTRALZ W/ SODIUM
BISULFITE THEN FLUSH TO SEWER W/LG AMT H₂O. FED STATE/LOCAL LAW
S
TAKE PRECEDENCE

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to the
ir
particular situation.