

EASTMAN KODAK COMPANY -- 102 0072 EKTACHROME R-3 FIRST AND COLOR DEVELOPER STARTER -- 6750-01-202-2939

=====
Product Identification
=====

Product ID:102 0072 EKTACHROME R-3 FIRST AND COLOR DEVELOPER STARTER

MSDS Date:04/07/1993

FSC:6750

NIIN:01-202-2939

MSDS Number: BGQML

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country

:US

Info Phone Num:716-477-3194

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 60-65%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM BROMIDE

CAS:7

647-15-6

RTECS #:VZ3150000

Fraction by Wt: 35-40%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN; LOW HAZARD FOR RECOMMENDED HANDLING. INHALATION: EXPECTED TO BE A LOW HAZARD F

OR RECOMMENDED

HANDLING. INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.

Effects of Overexposure:EYES: TRANSIENT IRRITATION. SKIN: LOW HAZARD

FOR RECOMMENDED HANDLING. INHALATION: EXPECTED TO BE A LOW HAZARD

FOR RECOMMENDED HANDLING. INGESTION: EXPECTED TO BE A LOW INGESTION HAZARD.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF SYMP

TOMS OCCUR,

GET MEDICAL ATTENTION. SKIN: WASH AREA WITH SOAP AND WATER. IF

SYMPTOMS DEVELOP, GET MEDICAL ATTENTION. INHALATION: IF

SYMPTOMATIC, MOVE TO FRESH AIR. IF SYMPTOMS PERSISTS, GET MEDICAL

ATTENTION. INGESTION: DRINK 1-2 GLASSES OF WATER. GET MEDICAL

ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:NONCOMBUSTIBLE LIQUID. USE MEDIA APPROPRIATE FOR SURROUNDING MATERIALS.

Fire Fighting Procedures:

WEAR SELF-CONTAINED BREATHING APPARATUS AND

PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL,

THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE

THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM FIRE AND EXCESSIVE HEAT. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:GOOD GENERAL VENTILATION (10 AIR CHANGES/HOUR) SHOULD BE USED.

VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS.

Protective Gloves:IMPERVIOUS GLOVES TO AVOID SKIN CONTACT.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:PROVIDE EYE WASH STATION, SAFETY SHOWER, WASHING FACILITIES.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

UNIT ISSUE OF 8 OZ BOTTLE OF PRODUCT MAKES 12.5 GALLONS OF WORKING SOLUTION.

N.

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.353

pH:7.0

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID. ODORLESS.

Percent Volatiles by Volume:60-65

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY REASONABLY COME INTO CONTACT

Stability Condition to Avoid:FIRE OR EXCESSIVE HEAT MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS.

Hazardous Decomposition Products:HYDROGEN BROMIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE
AND FEDERAL REGULATIONS. IF NOT RESTRICTED, FLUSH TO SEWER WITH
LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the comp
iling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.