

EASTMAN KODAK CO. -- 186 2176,EKTPRNT 2 DEVL, PART D (PRE 3/84) -- 6750-01-214-4621  
===== Product Identification =====

Product ID:186 2176,EKTPRNT 2 DEVL, PART D (PRE 3/84)

MSDS Date:10/20/1984

FSC:6750

NIIN:01-214-4621

Kit Part:Y

MSDS Number: BGQSJ

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:AREA MAR

KETING & DISTRIBUTION CNTR

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM CARBONATE; WT % RANGE:35-40%

CAS:584-08-7

RTECS #:TS7750000

Fraction by Wt: 37.5%

Ingred Name:POTASSIUM HYDROXIDE (SARA I

II)  
CAS:1310-58-3  
RTECS #:TT2100000  
Fraction by Wt: 03.0%  
OSHA PEL:C, 2 MG/M3  
ACGIH TLV:C 2 MG/M3; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:POTASSIUM SULFITE; WT % RANGE:1-5%  
CAS:10117-38-1  
RTECS #:WT3530000  
Fraction by Wt: 03.0%

Ingred Name:1-HYDROXYETHYLIDENE-1,1-DIPHOSPHONIC ACID DIPOTASSIUM SALT;  
WT % RANGE:1-5%  
CAS:21089-06-5  
Fraction by Wt: 03.0%

Ingred Name:WATER; WT % RANGE:55-60%  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 57.5%

=====  
Hazar  
ds Identification =====

LD50 LC50 Mixture:LD50 ORL RAT:0.5-5.0 G/KG  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Effects of Overexposure:INHALATION:NOT INDICATED BY  
MANUFACTURER;EYES:LIQUID CAUSES BURNS; SKIN:PROLONGED OR REPATED  
SKIN CONTACT MAY CAUSE SKIN IRRITATION AND/OR BURNS; INGESTION:MAY  
BE HARMFUL AND MAY CAUSE BURNS.

=====  
First Aid Measures =====

First A  
id:INHALATION:REMOVE TO FRESH AIR,TREAT SYMPTOMATICALLY & GET  
MEDICAL ATTN IF SYMTOMS PERSIST; EYES:IMMEDIATELY FLUSH W/PLENTY OF  
WATER FOR AT LEAST 15 MIN & GET MED ATTN IF SYMPTOMS PERSIST;  
SKIN:FLUSH W/WATER.IF IRRITATION OR AN ALLERGIC REACTION  
DEVELOPS,GET MED ATTN; INGESTION:DO NOT INDUCE VOMITING.IF  
CONSCIOUS GIVE ONE GLASS OF MILK OR WATER.NEVER GIVE ANYTHING BY  
MOUTH TO UNCON.GET MED ATTN.

=====  
Fire Fighting Measures =====

Fla

sh Point:NONE

Extinguishing Media:NOT COMBUSTIBLE:USE MEDIA SUITABLE FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIP.ELIM IGN SOURCES.EVACUATE UNPROTECTED PERSONS;SM SPILLS:ABSORB W/INERT ABSORBENT & NEUTRALIZE Q/SODIUM BISULFATE.FLUSH TO SEWER W/LG MATS OF H\*20;LG SPILLS:CONTAIN W/DIKE & TRANS FER TO APPROPRIATE CONTAINERS FOR LATERDISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA.PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:WARNING!CAUSES EYES BURNS.CAUSES SKIN IRRITATION.AVOID EYES,SKIN & CLOTHING CONTACT.AVOID CONTACT WITH ST RONG ACIDS.KEEP OUT OF REACH OF CHILDREN.IF SWALLOWED DON'T INDUCE VOMIT; PH: >13.0

===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL(GEN./LOCAL EXHAUST) AS NECESSARY TO CONTROL MIST

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:NORMAL FULL WORK CLOTHING COVERING ARMS,LEGS;NO SKIN CONTACT

Supplemental Safety and Health

ITEM HAS 7 PARTS IN THE KIT UNTIL NOV 80 UNDER CAT #121 6407.AFTER NOV 80 MFR C

HANGD CAT # TO 186 2176 AS WELL AS FORMULATION OF THIS

PART. SEE PNI 'H' FOR NEW PART,SAME NSN;THIS ENTRY IS OF EKTAPRINT 2 DEVELOPER,PART D;THIS PART MAY BE MARKED WITH 186 2051;

KEY1:C2;SOLUTION #4487 REMAINS THE SAME;YIELDS 1 GAL.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:>100C/>212F

Vapor Pres:20

Vapor Density:0.6

Spec Gravity:1.44

pH:13.0

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS SOLUTION; ODORLESS

Percent Volatiles by Volume:55%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS.

Stability Condition to Avoid:HIGH TEMPERATURE/HEAT

Hazardous Decomposition Products:COMBUSTION MAY PRODUCE OXIDES OF  
CARBON, AND SULFUR

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN FULL ACCORD WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS.MFG SUGGEST  
S

NEUTRALIZE WITH SODIUM BISULFATE & FLUSH TO SEWER WITH EXCESS  
WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume res

ponsibility for the suitability of this information to their  
particular situation.