

RANDOLPH PRODUCTS CO. -- ALCOHOL (TT-I-735) -- 6810-01-220-9907

=====
Product Identification
=====

Product ID:ALCOHOL (TT-I-735)

MSDS Date:11/12/1985

FSC:6810

NIIN:01-220-9907

MSDS Number: BGQWD

=== Responsible Party ===

Company Name:RANDOLPH PRODUCTS CO.

Address:PARK PLACE EAST

City:CARLSTADT

State:NJ

ZIP:07072

Info Phone Num:201-438-3700

Emergency Phone Num:201-438-3700

CAGE:77672

=== Contracto

r Identification ===

Company Name:RANDOLPH PRODUCTS CO

Address:701 12TH ST

Box:830

City:CARLSTADT

State:NJ

ZIP:07072-0830

Country:US

Phone:201-438-3700

CAGE:77672

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 99.6%+

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:WATER (OBTAINED FROM SPECS TT-I-735A)

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 0.4%/MAX

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:IRRITATION;SKIN:DRYNESS,CRACKING
SKIN;INHALATION:IRRITATION OF NOSE &
THROAT,DROWSINESS,DIZZINESS,HEADACHE;INGESTION:GASTRO-INTESTINAL
CRAMPS,NAUSEA,DIARRHEA.
Explanation of Carcinogenicity:ISOPROPYL ALCOHOL MANUFACTURE (STRONG
ACID PROCESS) IS HUMAN CARCINOGEN.
Effects
of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE NOTED

=====
First Aid Measures
=====

First Aid:EYES/SKIN:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES.REMOVE
CONTAMINATED CLOTHING.IF IRRITATION PERSISTS,SEE
DOCTOR;INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF
NEEDED;INGESTION:SEEK MEDICAL ATT ENTION IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Poi
nt:57F,14C
Lower Limits:2
Upper Limits:12
Extinguishing Media:SAND,FOAM,CO*2,DRY CHEMICAL
Fire Fighting Procedures:AVOID BREATHING VAPOR OR FUMES.USE AIR
SUPPLIED RESPIRATOR FOR ENCLOSED AREAS.COOL FIRE EXPOSED CONTAINERS
WITH WATER.
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. CAN TRAVEL TO
DISTANT IGNITION SOURCES AND IGNITE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.WEAR APPROVED
RESPIRA
TOR.CONTAIN SPILL WITH INERT ABSORBENT.PLACE IN APPROPRIATE
DISPOSAL CONTAINER.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP IN DRY,WELL VENTILATED AREA,AWAY
FROM HEAT & IGNITION SOURCES.KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:GROUND CONTAINERS & EQUIPMENT. EMPTY CONTAINERS ARE
HAZARDOUS,DO NOT CUT OR WELD.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WEAR NIOSH/MSH

A APPROVED RESPIRATOR IF TLV IS
EXCEEDED.

Ventilation:EXPLOSION PROOF EXHAUST VENTILATION AT POINT OF RELEASE.

Protective Gloves:NEOPRENE

Eye Protection:GOGGLES

Other Protective Equipment:COVERALLS & BOOTS

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE
CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=80.C, 176.F

Melt/Freeze Pt:=-88.9C, -128.F

Vapor Pres:34

Vapor Density:>1

Spec Gravity:0.8

Evaporation Rate & Reference: