

MAGNAFLUX CORPORATION -- SKL-LO SPOTCHECK PENETRANT (LOW ODOR) -- 6850-01-266-4553

=====
Product Identification
=====

Product ID:SKL-LO SPOTCHECK PENETRANT (LOW ODOR)

MSDS Date:08/19/1988

FSC:6850

NIIN:01-266-4553

MSDS Number: BGRYY

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W.LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:312-867-8000

Emergency Phone Num:312-867-8000

Preparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES (PETROLEUM),CATALYTIC REFORMER FRACTIONATER
RESIDUE,LOW BOILING

CAS:64877-31-6

Fraction by Wt: 10.0%

Ingred Name:PARAFFIN OILS

CA

S:64771-72-8
Fraction by Wt: 40.0%

Ingred Name:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: 02.0%
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:UNIDENTIFIED COMPONENTS;PER MFR,CONTAINS NO OTHER
INGREDIENT SUSPECTED OF BEING HAZARDOUS I/A/W INFO IN
29CFR1910.1200

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE:IRRITATING TO SKIN &
EYES;S

IGNIFICANT AMOUNT OF VAPOR INHALATION CAN RESULT IN
CLUMSINESS & POOR JUDGEMENT,WITH RESULTING DANGER TO THE
VICTIM.MUCH LIKE ALCOHOL EFFECT.

Effects of Overexposure:INHALATION:CAUSES
DIZZINESS,NAUSEA,DROWSINESS,FROM INHALATION OF SPRAY MIST;
SKIN:CAUSES IRRITATION,DISSOLVES SKIN OILS.POSSIBLE DERMATITIS ON
FREQUENT OR PROLONGED EXPOSURE; EYES:MODERATE IRRITATION BY
CONTACT OF LIQUID OR SPRAY; INGESTION:LOW TOXICITY,BUT HAZARDOUS IF
ASPIRATED INTO LUNGS BY INGESTION
OR VOMITING.

Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF NOT BREATHING,GIVE CPR.IF
BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:WASH OFF IN FLOWING WATER
OR SHOWER.RMV CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.USE
SOOTHING L OTION; EYES:FLUSH EYES WITH A STEADY,GENTLE FLOW OF
WATER.GET MEDICAL ASST; INGESTION:DO NOT INDUCE VOMITING.IF VOMIT
IS

INHALED,IT MAY CAUSE ASPHYXIATION.GET MED ATTN IMMEDIATELY;IN
EMERGENCY CALL MD

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F/>93.3C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE,FOAM

Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB
LIQUID WITH COMMERCIAL ABSORBENT.TRANSFER WASTE MATL IN SALVAGE
TANKS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL
VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP
CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT
HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.DO
NOT SPRAY INTO FLAME,ARCS,OR RED HOT SURFACES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE.IN
CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP CONCENTRATION
BELOW LIMITS.

Protective Gloves:NITRILE RUBBER GLOVES

Eye Protection:FULL GOGGLES

Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN
EXHAUST VENT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.LAUNDER
CONTAMINATED CLOTHES BEFORE RE-USE.

Supplemental Safety and Health

NSN (ESTBLSHD 1987) FOR KIT/SET UNDER TYPE II,METHOD B OF
MIL-I-25135D.SET CONSISTS OF TWO PARTS(SKL-LO PENETRANT AND EITHER
ZE-3 OR ZE-4B EMULSIFIER);QPL-25135-15 QUALIFIED THESE PRODUCTS

FOR
TYPE II ,METHOD B;EACH PART ALSO AVAILABLE SEPARATELY UNDER
SEPARATE NSNS;KEY1:X01;THIS IS SKL-LO;SEE PNI B&C FOR ZE-3 & ZE-4B.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:400F/204C
Vapor Pres:1.0
Spec Gravity:0.88
Solubility in Water:NEGLIGIBLE
Appearance and Odor:DARK RED LIQUID,LOW ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stabi
lity Condition to Avoid:HEAT,HIGH TEMPERATURES
Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE
D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES PROHIBIT
DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX
WASTEWATER SYSTEM.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.