

MAGNAFLUX CORPORATION -- ZL-1D ZYGLO PENETRANT -- 6850-01-268-6698

===== Product Identification =====

Product ID:ZL-1D ZYGLO PENETRANT

MSDS Date:05/28/1986

FSC:6850

NIIN:01-268-6698

MSDS Number: BGSCM

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W.LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656

Country:US

Info Phone Num:312-867-8000

Emergency Phone Num:312-867-8000

Pre

parer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

===== Composition/Information on Ingredients =====

Ingred Name:KEROSENE

CAS:8008-20-6

RTECS #:OA5500000

Fraction by Wt: 10.0%

ACGIH TLV:100MG/CUM

Ingred Name:UNIDENTIFIED COMPONENTS

Fraction by Wt: 90.0%

===== Hazards Identific

ation =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:IRRITATES EYES.
Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA;
SKIN:LIQUID IRRITATES BY DISSOVLING SKIN OIL; EYES:VAPORS/LIQUID
CAUSES IRRITATION; INGESTION:CAUSES GASTRIC UPSET.
Medical Cond Aggravated by Exposure:NOT KNOWN

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING I
S DIFFICULT,GIVE
OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING
WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN;
EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING
WATER,AND GET MEDICAL ATTENTION; INGESTION:GET MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:200F/93C
Lower Limits:6.0%
Upper Limits:1.0%
Extinguishing Media:CARBON DIOXIDE,FOAM
Fire Fighting Pro
cedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT
SPRAY WATER ON BURNING PRODUCT.
Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB
LIQUID WITH CO
MMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE
TANKS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL
VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP
CONTAINERS TIGHTLY CLOSED.
Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE UUSING.DO
NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection ===

=====

Respiratory Protection:WEAR RESPIRATOR WITH FILTER CARTRIDGE IF
SPRAYING IN UNVENTILATED AREA.
Ventilation:GENERAL VENTILATION OF 1-3 CHANGES PER HOUR,WHEN SPRAYED.
Protective Gloves:NITRILE RUBBER GLOVES
Eye Protection:FULL GOGGLES
Other Protective Equipment:NOT KNOWN
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING OR USE.LAUNDER
CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health
NSN FOR TYPE I,METHOD D,LEVEL 1 OF MIL-I-25135D;QPL-25135-15 QUALIFIED

THIS PRODUCT FOR TYPE I,METHODS B/C/D,LEVEL 1;THE DATA OF ZL-1D
PENETRANT ALSO DESCRIBED UNDER KIT'S NSN OF TYPE I,METHOD D,LEVEL
1;TYPE I,METH B,LVL 1 EMULSIFIER:ZE-3E/ZE-4B AND TYPE I,METH D,LVL
1 EMULSIFIER:ZR-10A/ZR-10B.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:410F/210C
Vapor Pres:1.0
Spec Gravity:0.92
Solubility in Water:NEGLIGIBLE
Appearance and Odor:GREEN OILY LIQUID,PETROLEUM DISTALLATES ODOR
Percent Volatiles by Vo
lume:10.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NOT KNOWN TO MFR.HOWEVER,AVOID STRONG OXIDIZERS.
Stability Condition to Avoid:HEAT,HIGH TEMPERATURES
Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE
D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE

FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES PROHIBIT
DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX
TREATMENTSYSYSTEM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
docu

ment should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.