View NSN Online: https://aerobasegroup.de/nsn/6850-01-268-6706

Product ID:ZL-27A ZYGLO PENETRANT (PRE 11/1988) MSDS Date:07/17/1986 FSC:6850 NIIN:01-268-6706 **MSDS Number: BGSDD** === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W. LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656-3504 Country:US Info Phone Num:807-867-8000 Emergency Phone Num:807-867-8000 Preparer's Name: BRUCE C. GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:DISTILLATES,(PETROLEUM)HYDROTREATED MIDDLE CAS:64742-46-7 RTECS #:JN9379645 Fraction by Wt: 10.0%

Ingred Name:KEROSENE CAS:8008-20-6 RTECS #:OA550 0000 Fraction by Wt: 5.0% ACGIH TLV:100MG/CUM

Ingred Name:DISTILLATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER RESIDUES,LOW BOILING CAS:68477-31-6 Fraction by Wt: 25.0%

Ingred Name:UNIDENTIFIED COMPONENTS Fraction by Wt: 60.0%

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES,MILDLY. Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE TO BREATHING PAS

SAGES; EYES:LIQUID CONTACT MAY CAUSE IRRITATION; SKIN:SOLVENT IN THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN; EYES:IMM EDIAT ELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING

ELY KINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING WATER,AND GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>200F/>93C Extinguishing Media:CARBON DIOXIDE,FOAM. Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT SPRAY ON BURNING PRODUCT. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

============= Accidental Rele

ase Measures =================

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

Handling and Storage Precautions: STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL D AMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: DO NOT BREATHE VAPORS. DO NOT SMOKE WHILE USING. DO NOT HEAT ABOVE 130F(54C). AVOID FREQUENT OR PROLONGED SKIN CONTACT. Respiratory Protection: WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS, WEAR A FULL MASK WITH SEPARATE AIR SUPPLY. Ventilation: GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT. Protective Gloves:NITRILE RUBBER GLOVES. Eye Protection: FULL GLASSES. WHEN SPRAYING OR POURING. Other Protective Equipment: EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING OR USE. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health NSN FOR TYPE I, METHOD D, LEVEL 3 MATERIAL OF MIL-I-25135D ZL-27A PENETRANT IS A QUALIFIED PRODUCT OF QPL-25135-15 FOR TYPE I, METHOD D,LVL 3;THE QPL SPECIFIED THE PENETRANT CAN ALSO BE A PART OF KIT W/Z R-10B EMU LSIFIER;SEE PNI A FOR OTHER QUALIFIED PENETRANT FOR SAME TYPE, METHOD & LEVEL. HCC:N1 Boiling Pt:B.P. Text:410F/210C Vapor Pres:0.5 @100F

Vapor Density:>1.0 Spec Gravity:0.95 Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN LIQUID WITH PETROLEUM DISTILLATES ODOR. Percent Volatiles by Volume:5.0%

Stability Indicator/Materials to Avoid:YES MFR STAT

ED "NONE". Stability Condition to Avoid:HEAT,HIGH TEMPERATURES. Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,PUR IFY RINSINGS W/MAGNAFLUX WASTEWATER TR

EATMNT SYSTM

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their part

icular situation.