View NSN Online: https://aerobasegroup.de/nsn/6850-01-268-6714

Product ID:ZR-10A REMOVER (HYDROPHILIC EMULSIFIER) MSDS Date:05/28/1986 FSC:6850 NIIN:01-268-6714 **MSDS Number: BGSDX** === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656 Country:US Info Phone Num:312-867-8000 Emergency Phone Num:312-867-8000 Preparer's Name: BRUCE C. GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:2-(2-BUTOXYETHYL) ETHANOL CAS:112-34-5 RTECS #:KJ9100000 Fraction by Wt: 200F/>93C Extinguishing Media:CARBON DIOXIDE,FOAM,WATER Fire Fighting Proc edures:KEEP CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

Handling and Storage Precautions: STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: DO NOT BREATHE VAPORS. DO NOT SMOKE WHILE USING. DO NOT HEAT ABOVE 130F(54C). AVOID FREQUENT OR PROLONGED SKIN CONTACT. Respiratory Protection:WEAR A RE SPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS, WEAR A FULL MASK WITH SEPARATE AIR SUPPLY. Ventilation: GENERAL VENTILATION TO KEEP BELOW TLV LIMITS. Protective Gloves:NITRILE RUBBER GLOVES Eye Protection: FULL GOGGLES Other Protective Equipment: EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health NSN FOR TYPE I, METHOD D, LEVEL 1 OF MIL-I-25135; QPL-251 35-15 HAS QUALIFIED ZR-10A FOR TYPE I, METH D, LEVELS 1, 2, 3, & 4; THIS PRODUCT IS HYDROPHILIC EMULSIFIER; THIS PRODUCT IS ALSO AVAILABLE IN SETS WITH SEVERAL PENETRANTS: ZR-10A OR ZR-10B IS NOT REMOVER BUT WATER SOLUBLE EMULSIFIER. HCC:V5 Boiling Pt:=204.4C, 400.F Vapor Pres:1.0

Vapor Pres:1.0 Spec Gravity:0.9 pH:7.0 Solubility in Water:COMPLETE Appearance and Odor:PINK OILY LIQUID

========= Stability and Reactivity Dat

Stability Indicator/Materials to Avoid:YES NOT KNOWN TO MFR. Stability Condition to Avoid:HEAT,HIGH TEMPERATURES Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN.

 Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS.IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN T
HE SEWER,P URIFY RINSINGS WITH MAGNAFLUX WASTEWATER SYSTEM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.