

OMNITECH INTERNATIONAL,INC. -- PENETRATING OIL -- 9150-00-529-7518

=====
Product Identification
=====

Product ID: PENETRATING OIL

MSDS Date: 06/17/1988

FSC: 9150

NIIN: 00-529-7518

MSDS Number: BGSMW

=== Responsible Party ===

Company Name: OMNITECH INTERNATIONAL, INC.

Address: 800 N ACADIA RD

City: THIBODAUX

State: LA

ZIP: 70301

Country: US

Info Phone Num: 504-446-2003

Emergency Phone Num: 504-446-2003

CAGE: KO

342

=== Contractor Identification ===

Company Name: OMNITECH INTERNATIONAL INC

Address: 800 N ACADIA RD

City: THIBODAUX

State: LA

ZIP: 70301

Country: US

Phone: 504-446-2003

CAGE: KO342

Company Name: QPL INC, FORMERLY OMNITECH INTERNATIONAL, INC.

Address: 800 N. ACADIA ROAD

Box: City: THIBODAUX

State: LA

ZIP: 70301

Country: US

Phone: 504-394-8440

CAGE: 0AD61

=====
Composition/Information on Ingredients
=====

Ingred Name: LIGHT PETROLEUM DISTILLATES

Fraction by Wt: 100%

Other REC Limits: 100PPM

O

SHA PEL:100 PPM(STODDARD SOL
ACGIH TLV:100 PPM(STODDARD SOL

Ingred Name:CARBON DIOXIDE (PROPELLANT)
CAS:124-38-9
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LOCAL VENTILATION AT THE WORKSITE;MECHAN
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CENTRAL NERVOUS SYSTEM DEPRESSANT. SEE
A LSO SIGN AND SYMPTO
MS OF OVEREXPOSURE.
Effects of Overexposure:EYES:SLIGHT TO MODERATE IRRITATION,SKIN:
MODERATELY IRRITATING,CAUSES REDNESS AND
DRYING;INHALATION:IRRITATING TO MUCOUS MEMBRANES AND RESPIRATORY
TRACT WILL PRODUCE SYMPTOMS OF INTOXICATION SUCH AS H
EADACHES,DIAPHRAGMATIC NAUSEA,VOMITING AND LOSS OF COORDINATION.
Medical Cond Aggravated by Exposure:PRE-EXISTING DERMATITIS.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH PLENTY OF WATER;SKIN:
WASH WITH SOAP AND
WATER.REMOVE CONTAMINATED CLOTHING;INHALATION:REMOVE TO FRESH
AIR.GIVE OXYGEN/CPR IF NEEDED.GET MEDICAL ATTENTION;INGESTION:DO
NOT INDUCE VOMIT SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:N/R,AEROSOL
Extinguishing Media:DRY, CHEMICAL,CO2,FOAM,WATER SPRAY.
Fire Fighting Procedures:USE WATER SPRAY TO COOL CONTAINERS.USE
SMOTHERING TECHNIQUE FOR EXTINGUISHING. DO NOT USE A FORCED WATER
STREAM DIRECTLY ON OIL
FIRES. WEAR SCBA.
Unusual Fire/Explosion Hazard:FLOWING PETROLEUM PRODUCTS CAN BE IGNITED
BY STATIC ELECTRICITY.CONTENTS UNDER PRESSURE.CAN EXPLODE IF
HEATED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES VENTILATE.ABSORB IN
INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 129F(49

C).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA-APPROVED RESPIRATORY DEVICE
APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:MECHANICAL (GENERAL) VENTILATION.USE EXPLOSION-PROOF FAN.

Protective Gloves:NEOPRENE,PVA

Eye Protection:GOGGLES

Other Protective Equipment:NONE

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

NONE

=====

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:330-515F

Melt/Freeze Pt:M.P/F.P Text:-22F(-30C)

Vapor Pres: