

TURNER/THE COOPER GROUP -- QUICK START DIESEL STARTING FLUID, LP-535 --
2910-00-646-9727

===== Product Identification =====

Product ID:QUICK START DIESEL STARTING FLUID, LP-535

MSDS Date:06/01/1987

FSC:2910

NIIN:00-646-9727

MSDS Number: BGSTP

=== Responsible Party ===

Company Name:TURNER/THE COOPER GROUP

Address:821 PARK AVENUE

City:SKCAMORE

State:IL

ZIP:60178-2419

Emergency Phone Num:815-895-454

5

CAGE:LO734

=== Contractor Identification ===

Company Name:QUICK START PRODUCTS LTD

Address:HIGHWAY 251 SOUTH

Box:City:ROCHELLE

State:IL

ZIP:61068

Country:US

Phone:815-562-5414

CAGE:78280

Company Name:TURNER CO DIV OF CLEANWELD PRODUCTS CO

Address:821 PARK AVE

Box:6200

City:SYCAMORE

State:IL

ZIP:60178-2419

Country:US

Phone:815-895-4545

CAGE:61112

Company Name:TURNER/THE COOPER GROUP

Address:821 PARK AVENUE

Box:City:SKCAMORE

State:IL

ZIP:60178-2419

CAGE:LO734

===== Composition/Informat

ion on Ingredients =====

Ingred Name:ETHYL ETHER (SARA III)
CAS:60-29-7
RTECS #:KI5775000
Fraction by Wt: 93%.
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400PPM/500STEL; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ETHYLENE (SARA III)
CAS:74-85-1
RTECS #:KU5340000
Fraction by Wt: 6.5%
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:POLYALKYLENE GLYCOL
Fraction by Wt: 0.5%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES I
ngestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYE & RESPIRATORY IRRITANT
ANESTHETIC & ASPHYXIAN; CAN CAUSE FISSURED DERMATITIS; CHRONIC
EFFECTS: ANOREXIA,EXHAUSTION,HEADACHE, DROWINESS, DIZZINESS,
EXCITATION & PSYCHIC DISTURBANCES.ALBUMIN URIA HAS BEEN REPORTED
CHRONIC EXPOSUREMAY CAUSE AN INCREASED SUSCEPTIBILITY TO ALCOHOL.

Effects of Overexposure:EYES: IRRITATION & CONJUNCTIVITIS POSSIBLE;
SKIN: MILD IRRITATION D

RYING, CRAKING(FISSURED DERMATITIS); INHAL:
UPPER RESPIRATORY IRRITANT, HEADACHE, DIZZINESS, NAUSEA, VOMITING,
IRREGULAR RESPIRATION, DEPRESSION, EXCITATION & PALLOR &
UNCONSCIOUSNESS; INGEST: SIMILAIR TO INHALATION

Medical Cond Aggravated by Exposure:ANY LAIENT ALLERGY, SENSITIVITY OR
RESPIRATORY DYSFUNCTION.

===== First Aid Measures =====

First Aid:EYES: IRRIGATE EYES W/WATER FOR 15 MIN.; SKIN: WASH AFFECTED
AREAS W/SOAP & WATER; I

NHAL:REMOVE TO FRESH AIR. GIVE O**2/CPR AS
SITUATION DICTATES. INGEST: GET MEDICAL ATTN. IMMEDIATELY AS PROMPT
TREAT MENT REQUIRED TO MINIMIZE "CNS" EFFECTS

===== Fire Fighting Measures =====

Flash Point:N/R FOR CYLINDER
Autoignition Temp:Autoignition Temp Text:356F
Lower Limits:1.85
Upper Limits:40.0
Extinguishing Media:CARBON DIOXIDE, FOAM
Fire Fighting Procedures:COOL EXPOSED CYLINDER W/ WATER SPRAY. UNIT
WILL RELIEVE PRESSURE & 200F/93C +/- 5F
RELEASING FLAMMABLE ETHER
VAPORS & ETHYLENE GAS!
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE.RELEASED
VAPOR/GAS IS HIGHLY FLAMMABLE & EASILY IGNITED.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.VENTILATE AREA TO
REMOVE FUMES. WEAR SELF-CONTD. BREAHING APPARATUS IF EXPOSURE MAY
LEAP TO EXCEEDING "TLV". ALLOW SPILLAGE TO EVAPORATE. FLUSH LARGE
SPILLS W/WATER TO REMOV E RESIDUAL FILM(0.5% OF
CYLINDER CONTGNT)

===== Handling and Storage =====

Handling and Storage Precautions:DP NOT STORE AT TEMPERATURES EXCEEDING
175F/79.4C. DISCONNECT GLOW PLUG DURING STORAGE.
Other Precautions:PROTECTIVE CLOTHING SHOULD BE MADE EITHER FROM A
SPECIAL RUBBER COMPOUND RESISTANT TO SWELLING BY ETHER

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UPPER LIMIT DEVICE: TO 1000 PPM-ANY CHEMICAL
CARTRIDGE RESPIRA
TOR W/ORGANIC VAPOR CARTRIDGE(S) OR ANY
SUPPLIED-AIR RESPIRATOR OR SELF-CONTD. BRTHNG APPARATUS.
Ventilation:LOCAL EXHAUST OF EXPLOSION PROOF DESIGNED.
Protective Gloves:NONE REQUIRED, ALTHOUGH RECOMMENDED.
Eye Protection:SAFETY GLASSES/CHEMICAL GOGGLES.
Other Protective Equipment:AS REQUIRED TO MINIMIZE EXPOSURE FOR &AS AT
HAND.
Work Hygienic Practices:FOLLOW THOSE ESTABLISHED BY INDUSTRIAL HYGIENSE
& SAFETY FOR USE OF HIS MATERIAL AS WELL AS TECHNICAL MANUAL
Supplemental Safety and

Health

===== Physical/Chemical Properties =====

HCC:G2

Boiling Pt:B.P. Text:94F/34.4C

Melt/Freeze Pt:M.P/F.P Text:-176.8F

Vapor Pres:8.8PSIA70F

Vapor Density:2.6

Spec Gravity:0.695 @ 77F

Solubility in Water:MODERATE

Appearance and Odor:ETHER ODOR, BUT COLORLESS

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:EXCESS HEAT(175

F/79.4C & ABOVE) AS WELL AS

IGNITION SOURCES.

Hazardous Decomposition Products:CARBON MONOXIDES CARBON DIOXIDE, WATER VAPOR, VARIOUS ALDHYDES, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF CYLINDER CONTENTS VIA SLOW RELEASE TO ATMOSPHERE. DONOT INCINERATE CYLINDERS! FOLLOW ALL APPLICABLE FEDERAL, STATE , LOCAL-REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is

formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.