

AVIATION FLUIDS SERVICE, INC. -- TURBO 10 -- 9150-00-159-5012

=====
Product Identification
=====

Product ID:TURBO 10

MSDS Date:10/22/1985

FSC:9150

NIIN:00-159-5012

MSDS Number: BGTJV

=== Responsible Party ===

Company Name:AVIATION FLUIDS SERVICE, INC.

Address:950 KINGSLAND

City:ST LOUIS

State:MO

ZIP:63130

Country:US

Info Phone Num:314-722-2888

Emergency Phone Num:314-721-2888

CAGE:0AG11

=== Contr

actor Identification ===

Company Name:AVIATION FLUIDS SERVICE INC

Address:950 KINGSLAND AVE

Box:2489

City:ST LOUIS

State:MO

ZIP:63114

Country:US

Phone:314-721-2888

CAGE:0AG11

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 26-32%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:METHYLLACRYLATE COPOLYMER

Fraction by Wt: 68-74%

=====
Hazard

s Identification =====

LD50 LC50 Mixture:ACUTE ORAL LD50 RAT >5 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SLIGHT TO MODERATE IRRITATION OF SKIN AND EYE.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS CHEMICAL IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE AND SKIN IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF

DERMATITIS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR. CALL A PHYSICIAN. SKIN: WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CALL A PHYSICIAN. EYE: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALLA PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER TO DRINK. GIVE NOTHING BY MOUTH IF UNCONSCIOUS,CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:375F,190C

Extinguishing Media:CARBON DIOXIDE, ALCOHOL FOAM, DRY CHEMICAL

Fire Fighting Procedures:EVACUATE AREA, WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:TOXIC FUMES MAY BE GIVEN OFF WHEN MATERIAL IS EXPOSED TO FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: ABSORB ON SAND OR OTHER NON-COMBUSTIBLE ABSORBANT. PLACE IN DISPOSAL CONTAINER. LARGE SPILL: EVACUATE AREA. VENTILATE AREA. ELIMINATE IGNITION SOURCES. DIKE TO RETAIN SPILL. PICK UP FREE LIQUID WITH PUMP OR VACUUM. ABSORB RESIDUE

Neutralizing Agent:NONE RECOMMENDED

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, D

RY AREA, KEEP

CONTAINER TIGHTLY CLOSED WHEN NOT IN USE, PROTECT FROM PHYSICAL DAMAGE, MAXIMUM STORAGE TEMPERATURE IS 299F,93C.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT NIOSH/MSHA APPROVED RESPIRATOR BASED UPON CONTAMINATION LEVELS FOUND IN THE WORK PLACE. NONE REQUIRED FOR NORMAL OPERATIONS.

Ventilation:LOCAL AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN VAPOR AND MIST CONCENTRATIONS BELOW PELS EST. BY OSHA

Protective Gloves:RUBBER (IMPERVIOUS)

Eye Protection:SAFETY GLASSES OR SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING,DRINKING OR SMOKING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F,316C

Melt/Freeze Pt:M.P/F.P Text:25F,-4C

Vapor Pres: