

MET-L-CHEK COMPANY -- FP-95 A PENETRANT -- 6850-01-268-8788

===== Product Identification =====

Product ID:FP-95 A PENETRANT

MSDS Date:01/01/1997

FSC:6850

NIIN:01-268-8788

Kit Part:Y

MSDS Number: BGTLH

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Info Phone Num:310-450-1111

Emergency Phone Num:310-450-1111/800-4

24-9300(CHEMTREC)

Chemtrec Ind/Phone:(800)424-9300

CAGE:98733

=== Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

Contract Num:SP0450-99-M-NF20

CAGE:98733

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON,SEVERELY HYDROTREATED MIDDLE
DISTILLATE/HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7

RTECS #:JN

9379645

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT-PRESUMED NON-IRRITATING.

SKIN CONTACT-SLIGHTLY IRRITATING. INHALATION-VAPORS OR OIL MISTS
MAY CAUSE MILD IRRITATION

OF UPPER RESPIRATORY TRACT. INGESTION-MAY

RESULT IN VOMITING. ASPIRATION MUST BE AVOIDED.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN CONTACT-IRRITATION. INGESTION-POSSIBLE
VOMITING.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-FLUSH WITH WATER,
WASH WITH

SOAP & WATER. INHALATION-REMOVE TO FRESH AIR, PROVIDE

OXYGEN IF BREATHING IS DIFFICULT. INGESTION-DO NOT INDUCE VOMITING.

GET MED ICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=-98.9C, 210.F

Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON
DIOXIDE. DO NOT USE DIRECT STREAM OF WATER.

Fire Fighting Procedures:MATERIAL WILL NOT BURN UNLESS PREHEATED. DO
NOT ENTER CONFINED FIRE-SPACE WITHOUT FUL

L BUNKER GEAR, INCLUDING A

POSITIVE PRESSURE NIOSH APPROVED SELF-CONFINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH AN ABSORBENT SUCH AS CLAY, SAND,
OR OTHER SUITABLE MATERIAL. DISPOSE OF IN ACCORDANCE WITH FEDERAL
AND STATE REGULATIONS FOR OIL RESIDUE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY

FROM HEAT, OPEN FLAMES AND
OXIDIZING MATERIALS.

Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE EXCEEDS TLV, USE NIOSH APPROVED
RESPIRATOR TO PREVENT OVEREXPOSURE.

Ventilation:LOCAL EXHAUST: TO MAINTAIN TLV. MECHANICAL: TO MAINTAIN
TLV.

Protective Gloves:CHEMICAL RESISTANT TO MINIMIZE SKIN CONTACT.

Eye Protection:NO SPECIAL PROTECTION REQUIRED.

Other Protective Equipment:AS REQUIRED TO MINIMIZE SKIN CON
TACT.

Work Hygienic Practices:MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER
BEFORE EATING, DRINKING, SMOKING, OR USING TOILET.

Supplemental Safety and Health

THIS PRODUCT IS A TWO PART KIT. UNIT KIT IS ONE 55-GALLON DRUM OF
PENETRANT AND TWO 55-GALLON DRUMS OF EMULSIFIER.

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:>204.4C, 400.F

Melt/Freeze Pt:=-59.4C, -75.F

Spec Gravity:ABOUT 0.91

Evaporation Rate & Refer
ence:UNKNOWN(BUAC=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:YELLOW-GREEN LIQUID; SLIGHT HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL.

Stability Condition to Avoid:HEAT, OPEN FLAMES AND OXDIZING MATERIALS.

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND OTHER
UNIDENTIFIED ORGANIC COMPOUNDS.

Conditions to Avoid Polymerization:HEAT, OPEN FLAMES AND OXDIZING
MA

TERIALS.

===== Disposal Considerations =====

Waste Disposal Methods: PLACE IN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.