View NSN Online: https://aerobasegroup.de/nsn/3439-00-262-2670

Product ID:HOBART 10 1/8X14 IN 1 LB AES A5.1 MSDS Date:08/01/1985 FSC:3439 NIIN:00-262-2670 MSDS Number: BGTNW === Responsible Party === Company Name: HOBART BROTHERS COMPANY Address:600 W. MAIN STREET City:TROY State:OH ZIP:45373 Info Phone Num:513-339-6000 Emergency Phone Num:513-33 9-6000 CAGE:28835 === Contractor Identification === Company Name: HOBART BROTHERS CO Address:600 W MAIN ST HOBART SQUARE Box:City:TROY State:OH ZIP:45373 Country:US Phone:513-339-6000 CAGE:28835

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Other REC Limits:NONE OSHA PEL:10MG/M\*3(DUST,FUME) ACGIH TLV:5MG/M\*3(DUST,FUME)

Ingred Name:MANGANESE (SARA III) CAS:7439-96-5 RTECS #:OO9275000 Other REC Limits:NONE OSHA PEL:(C) 5 MG /M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Other REC Limits:NONE OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MAGNESIUM OXIDE CAS:1309-48-4 RTECS #:OM3850000 Other REC Limits:NONE OSHA PEL:15 MG/M3 PARTICULATE ACGIH TLV:10 MG/M3;TDUST; 9293

Ingred Name:POTASSIUM SILICATE CAS:1312-76-1 Other REC Limits:NONE

Ingred Name:SODIUM SILICATE CAS:1344-09-8 Other REC Limits:NONE

================== Hazards Identification

\_\_\_\_\_

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS
OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.
CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG
FIBROSIS,PNEUMOCONIOSIS. ARC RAYS CAN IN JURE EYES & BURN SKIN.
ELECTRIC SHOCK CAN KILL.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated b
y Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS.HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG SMOKERS.

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF NOT BREATHING,GIVE CPR.IF UNCONSCIOUS,GIVE OXYGEN. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

Extinguishing Media:USE MEDIA APPR

OPRIATE FOR SURROUNDING FIRE. Unusual Fire/Explosion Hazard:WELDING ARCS AND SPARKS CAN IGNITE CONBUSTIBLE PRODUCTS.

======================================
Spill Release Procedures: CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DOT APPROVED DISPOSAL CONTAINER.
======================================
Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOS URES.AVOID ELECTRICAL SHOCK BY MAINTAING DRY WORK AREA.
======================================
Respiratory Protection: FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.
Ventilation:LOCAL EXHAUST TO MAINTAIN BELOW TLV. Protective Gloves:WELDER'S GLOVES. Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS. Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM PROTECTOR,APRON,HAT,SHOUL DER PROTECTION. Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING,USING SANITARY FACILITIES. Supplemental Safety and Health NONE.
======================================
HCC:N1 Solubility in Water:INSOLUBLE Appearance and Odor:WELDING ROD.NO ODOR. 1/8 INCH DIAMETER BY 14 INCHES LONG.
======================================

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:FUMES OF MET

## ALS AND METAL OXIDES,CO,NO\*2,O\*3.

Waste Disposal Methods:DISPOSE OF FUMES,FLUX OR WELD GRINDING RESIDUE FROM THE WORK AREA OR FROM FILTERS IAW ALL APPLICABLE FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly o

r implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.