View NSN Online: https://aerobasegroup.de/nsn/8010-00-598-7669

TRIAD PAINT AND CHEMICAL CORP -- STAIN, TT-S-711C -- 8010-00-598-7669

Product ID:STAIN, TT-S-711C MSDS Date:01/01/1987 FSC:8010 NIIN:00-598-7669 MSDS Number: BGVQX === Responsible Party === Company Name: TRIAD PAINT AND CHEMICAL CORP Address:810 EVERGREEN AVENUE City:BROOKLYN State:NY ZIP:11207 Country:US Info Phone Num:(718) 443-2778 Emergency Phone Num:(718) 443 -2778 CAGE:33151 === Contractor Identification === Company Name: STEVEN INDUSTRIES Address:39 AVENUE C Box:8 **City:BAYONNE** State:NJ ZIP:07002-3417 Country:US Phone:201-437-6501 CAGE:33150 Company Name: TRIAD PAINT AND CHEMICAL CORP Address:810 EVERGREEN AVE Box:City:BROOKLYN State:NY ZIP:11207-1140 Country:US CAGE:33151

Ingred Name:PIGMENT Fraction by Wt: 6.6%

Ingred Name:VEHICLE Fraction by Wt: 93.4%

Ingred Name: MINERAL SPIRI

TS CAS:64741-41-9 Fraction by Wt: 62.4% ACGIH TLV:100 PPM

==

Health Hazards Acute and Chronic:VAPORS MIGHT BE IRRITATING TO EYES, NOSE AND THROAT. REPEATED EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, SLEEPINESS AND NAUSEA. DEFATTING TO SKIN. Effects of Overexposure:VAPORS MIGHT BE IRRITATING TO EYES, NOSE AND THROAT. REPEATED EXCESSIVE EXPOSURE MAY RESULT IN HEADACHE, DIZZINESS, SLEEPINESS AND NAUSEA.

First Aid:INHALATION: PROVIDE FRESH AIR AND REST. SKIN CONTACT: WASH WITH MILD SOAP AND WATER. USE EMOLLIENT CREAM OR LOTION. EYE CONTACT: WASH WITH GENTLE STREAM OF WATER FOR 10 MINUTES. SEE A DOCTOR.

Flash Point Method:PMCC Flash Point:105F/41C Lower Limits:1.0 Upper Limits:6.0 Extinguishing Media:FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedure s:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED RESPIRATORS. WATER STREAM WILL SPREAD OIL FIRES. Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION. VAPOR FORMS EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS.

Spill Release Procedures: AVOID FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. WIPE UP SPILL WITH INERT ABSORBENTS AND NON SPARKING TOOL

S. SAFELY DISCARD SATURATED ABSORBENTS. AVOID PROLONGED BREATHING OF VAPORS WHILE CLEANING UP SPILL.

Handling and Storage Precautions: AVOID OPEN FLAMES AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT. Other Precautions: DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. =========== Exposure Controls/Personal Protection == =========== Respiratory Protection: ORGANIC CANNISTER MASK OR AIR PACK IF VENTILATION IS ADEQUATE. Protective Gloves: NEOPRENE RUBBER GLOVES. Eye Protection: CHEMICAL SAFETY GOGGLES. Other Protective Equipment: MECHANICAL: W/APPROVED CLASS D EXPLOSION PROOF MOTOR AND SWITCHES. Supplemental Safety and Health Boiling Pt:B.P. Text:315,334,382 Vapor Pres:100F 1 Vapor Density:5.0 Spec Gravity:.901 Evaporation Rate & amp; Refer ence:.13 Solubility in Water:NEG Appearance and Odor:MAPLE COLOR LIQUID, HYDROCARBON ODOR. Percent Volatiles by Volume:72 Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:CO, CO2, ACID FUMES, AND SMOKE WHEN COMBUSTED. Waste Disposal Methods: DISPOSAL PROCEDURES MUST COMPLY WITH LOCAL, STATE

AND

FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to the ir

particular situation.