

AMERICAN OIL AND SUPPLY CO -- KS 7470;PRODUCT CODE:52002 -- 9150-00-448-5009

=====  
Product Identification  
=====

Product ID:KS 7470;PRODUCT CODE:52002

MSDS Date:09/02/1989

FSC:9150

NIIN:00-448-5009

MSDS Number: BGWKX

=== Responsible Party ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:238 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Info Phone Num:201-589-0250

Emergency Phone Num:

201-589-0250

Preparer's Name:LAB MANAGER

CAGE:92895

=== Contractor Identification ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:239 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Phone:201-589-0250

CAGE:92895

Company Name:WESTERN ELECTRIC GOVERNMENT SERVICE CO.

Box:20046

CAGE:0CSJ1

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 97-99%

Other REC Limits:5

MG/CUM  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL  
CAS:128-37-0  
RTECS #:GO7875000  
Fraction by Wt: 0-1%  
OSHA PEL:10 MG/M3  
ACGIH TLV:10 MG/M3; 9192

Ingred Name:METHACRYLIC ACID,COPOLYMER OF LAURYL AND STEARYL ESTERS  
Fraction by Wt: 0-1%

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRE-EXISTING CONDITI  
ONS MAY BE WORSEN  
Explanation of Carcinogenicity:NO DATA PER MSDS  
Effects of Overexposure:INHALE: NASAL IRRITATION, DIZZINESS, WEAKNESS,  
NAUSEA, HEADACHE, POSSIBLE UNCONCIOUSNESS; EYE/SKIN CONTACT:  
IRRITATION; INGEST: NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL  
IRRITATION.

=====  
===== First Aid Measures =====

First Aid:INHALE: REMOVE FROM FRESH AIR, IF BREATHING IS DIFFICULT,  
ADMINISTER OXYGEN, IF BREATHING HAS STOPPED, APPLY ARTIFICIAL  
RESP  
IRATION; EYE/SKIN: FLUSH WITH PLENTY OF WATER; INGEST: CONTACT  
A PHYSICIAN F OR DIRECTION, NEVER GIVE ANYTHING BY MOUTH TO AN  
UNCONCIOUS PERSON.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:400F,204C  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:CO\*2,FOAM,DRY CHEMICAL,WATER SPRAY.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED  
BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:DO NOT USE DIRECT S

TREAM OF WATER  
MATERIAL MAY FLOAT & REIGNITE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION. RECOVER FREE LIQUID. ADD ABSORBENT TO SPOLL AREA. COLLECT ABSORBENT. KEEP PRODUCT OUT OF WATERWAYS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE USUALLY REQUIRED.

Ventilation:NORMAL ROOM VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES  
Other Protective Equipment:PROTECTIVE CLOTHING,EYE WASH-FACILITIES,APRON AND BOOTS.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>400F,>204C

Vapor Pres:0.001

Vapor Density:13

Spec Gravity:0.88

Evaporation Rate & Reference: