

AMERICAN OIL AND SUPPLY CO -- KS 7470;PRODUCT CODE:52002 -- 9150-00-448-5009

===== Product Identification =====

Product ID:KS 7470;PRODUCT CODE:52002

MSDS Date:09/02/1989

FSC:9150

NIIN:00-448-5009

MSDS Number: BGWKX

=== Responsible Party ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:238 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Info Phone Num:201-589-0250

Emergency Phone Num:

201-589-0250

Preparer's Name:LAB MANAGER

CAGE:92895

=== Contractor Identification ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:239 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Phone:201-589-0250

CAGE:92895

Company Name:WESTERN ELECTRIC GOVERNMENT SERVICE CO.

Box:20046

CAGE:0CSJ1

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 97-99%

Other REC Limits:5

MG/CUM
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:2,6-DI-TERT-BUTYL-P-CRESOL
CAS:128-37-0
RTECS #:GO7875000
Fraction by Wt: 0-1%
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3; 9192

Ingred Name:METHACRYLIC ACID,COPOLYMER OF LAURYL AND STEARYL ESTERS
Fraction by Wt: 0-1%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRE-EXISTING CONDITIONS MAY BE WORSEN
Explanation of Carcinogenicity:NO DATA PER MSDS
Effects of Overexposure:INHALE: NASAL IRRITATION, DIZZINESS, WEAKNESS, NAUSEA, HEADACHE, POSSIBLE UNCONCIOUSNESS; EYE/SKIN CONTACT: IRRITATION; INGEST: NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL IRRITATION.

===== First Aid Measures =====

First Aid:INHALE: REMOVE FROM FRESH AIR, IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN, IF BREATHING HAS STOPPED, APPLY ARTIFICIAL RESPIRATION; EYE/SKIN: FLUSH WITH PLENTY OF WATER; INGEST: CONTACT A PHYSICIAN FOR DIRECTION, NEVER GIVE ANYTHING BY MOUTH TO AN UNCONCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:400F,204C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:CO*2,FOAM,DRY CHEMICAL,WATER SPRAY.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:DO NOT USE DIRECT S

TREAM OF WATER
MATERIAL MAY FLOAT & REIGNITE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. PROVIDE
ADEQUATE VENTILATION. RECOVER FREE LIQUID. ADD ABSORBENT TO SPOLL
AREA. COLLECT ABSORBENT. KEEP PRODUCT OUT OF WATERWAYS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE USUALLY REQUIRED.
Ventilation:NORMAL ROOM VENTILATION
Protective Gloves:IMPERVIOUS
Ey
e Protection:SAFETY GLASSES
Other Protective Equipment:PROTECTIVE CLOTHING,EYE
WASH-FACILITIES,APRON AND BOOTS.
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN.WASH
THOROUGHLY AFTER EACH USE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>400F,>204C
Vapor Pres:0.001
Vapor Density:13
Spec Gravity:0.88
Evaporation Rate & Reference: