View NSN Online: https://aerobasegroup.de/nsn/8030-01-033-1530

DOW CORNING CORP -- 93-118 RTV SILICONE SEALANT, PART B -- 8030-01-033-1530

Product ID:93-118 RTV SILICONE SEALANT, PART B

MSDS Date:09/04/1990

FSC:8030

NIIN:01-033-1530

Kit Part:Y

MSDS Number: BGWSM === Responsible Party ===

Company Name: DOW CORNING CORP Address: 3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI ZIP:48640 Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900 Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name: DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name: DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI ZIP:48611 Country:US

Phone:517-496-4388

CAGE:71984

======= Composition/Information on Ingredients ========

Ingred Name: SILICA, AMORPHO

US, DUST CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 19% Other REC Limits: NONE SPECIFIED OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3; 8990 Ingred Name:TRIMETHYLATED SILICA CAS:68909-20-6 Fraction by Wt: 24% Other REC Limits: 5 MG/M3 CEILING ========== Hazards Identification ================ Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE EFFECTS: DIRECT CONTACT WITH EYES MAY CAUS E TEMPORARY DISCOMFORT, CHRONIC EFFECTS:NONE KNOWN. Explanation of Carcinogenicity: NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN. Effects of Overexposure:EYES:TEMPORARY DISCOMFORT. SKIN:SINGLE PROLONGED EXPOSURE CAUSES NO EFFECT. SEVERAL REPEATED PROLONGED EXPOSURES CAUSES SLIGHT IRRITATION. INHALATION:NO IRRITATION TO NOSE OR THROAT EXPECTED. INGESTION: AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS SHOULD CAUSE NO INJURY. CHRONIC:NO KNOW N CHRONIC HEALTH EFFECTS. Medical Cond Aggravated by Exposure: MAY ENHANCE ALLERGIC CONDITIONS IN CERTAIN INDIVIDUALS. First Aid:EYES:FLUSH WITH WATER. SKIN:WIPE OFF AND FLUSH WITH WATER.

INHALATION:NO PROBLEM, INGESTION:NO PROBLEM.

============ Fire Fighting Measures =========================

Flash Point Method:OC Flash Point:>212F,>100C

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY

CHEMICAL. Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.
======== Accidental Release Measures ==========
Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUE, AN D PLACE IN APPROPIATE DISPOSAL CONTAINER.
============ Handling and Storage =============
Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED. Other Precautions:TRACES OF FORMALDEHYDE (CARCINOGEN) MAY FORM IF HEATED IN AIR ABOVE 300F (149C). PROVIDE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES. REVIEW OSHA FORMALDEHYDE REGU LATIONS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPIATE FOR EXPOSURE OF CONCERN. Ventilation:MECHANICAL (GENERAL) VENTILATION RECOMMENDED TO KEEP EXPOSURE LEVELS BELOW PEL. Protective Gloves:NONE SHOULD BE NEEDED. Eye Protection:SAFETY GLASSES AS MINIMUM. Other Protective Equipment:WORK CLOTHING TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. Work Hygienic Practic es:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health KEY1:N1. THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING. USE AT ELEVATED TEMPERATURES MAY REQUIRE ADDED PRECAUTIONS. THIS IS PART B OF A 2-PART KIT.FOR PART A, SEE PNI A, SAME NSN.

========= Physical/Chemical Properties ==========

HCC:V7 Vapor Pres: