

E/M CORPORATION -- CP-66;GREASE MOLYBDENUM.DISULFIDE -- 9150-00-753-4830

=====
Product Identification
=====

Product ID:CP-66;GREASE MOLYBDENUM.DISULFIDE

MSDS Date:11/20/1985

FSC:9150

NIIN:00-753-4830

MSDS Number: BGXDC

=== Responsible Party ===

Company Name:E/M CORPORATION

Address:HWY 52 NW,

Box:2200

City:WEST LAFAYETTE

State:IN

ZIP:47906

Country:US

Info Phone Num:313-463-2511

Emergency Phone Num

:317-463-2511

Preparer's Name:CHARLES J BEALL

CAGE:EMCOR

=== Contractor Identification ===

Company Name:E / M CO. DIV OF MORGAN CHEMICAL PRODUCTS INC

Address:100 COOPER CIR

Box:3969

City:PEACHTREE CITY

State:GA

ZIP:30269

Country:US

Phone:770-261-4835 / FAX: 770-631-0833

CAGE:8F024

Company Name:E/M CORPORATION

Address:2601 KENT AVE

Box:2400

City:WEST LAFAYETTE

State:IN

ZIP:47906

Phone:(317) 497-6100

CAGE:EMCOR

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLY

BDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
OSHA PEL:10 MG/M3 TDUST (MO)
ACGIH TLV:10 MG/M3 (MO); 8990

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,RESPIRATORY OR G.I. TRACT;REDNESS OR BLURRED VISION,G.I.
TRACT DISTURBANCE,NAUSEA,VOMITING
DIARRHEA.CHRONIC:DERMATITIS,IRRITATION.

E
Explanation of Carcinogenicity:NO DATA AVAILABLE.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

=====
===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP & WATER;EYES;FLUSH WITH PLENTY OF WATER
FOR ABOUT 15 MINUTES,CALL A PHYSICIAN. INGESTION;DO NOT INDUCE
VOMITING,KEEP WARM,GET MEDICAL ATTENTION,IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:388F/198C
Extinguishing Media:CO*2,FOAMDRY CHEMICAL,OR HALON.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:IRRITATION OR TOXIC VAPORS?MIST
INCLUDING,CO,CO*2,H*25,& SO*2.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:REMOVE ALL
IGNITION SOURCES;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER
FOR PROPER DISPOSAL.

==

===== **Handling and Storage**=====

Handling and Storage Precautions:STORE IN A COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM ACIDS,ALKALIS,OPEN FLAMES.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV.

Ventilation:LOCAL EXHAUST TO MAINTAIN PEL/TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES /GLASSES

Other Protective E

quipment:APRON,EYE-WASH FOUNTAIN.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT TAKE INTERNALLY.

Supplemental Safety and Health

===== **Physical/Chemical Properties**=====

HCC:V6

Spec Gravity:1.8

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GRAY/BLACK PASTE,MILD ODOR

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXTREME HE

AT,OPEN FLAMES

===== **Disposal Considerations**=====

Waste Disposal Methods:INCINERATION OR DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabi

lity for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.