

FLEET SUPPLIES, INC. -- DIESEL #2 -- 9140-00-286-5294

===== Product Identification =====

Product ID:DIESEL #2

MSDS Date:03/29/1987

FSC:9140

NIIN:00-286-5294

MSDS Number: BGXGZ

=== Responsible Party ===

Company Name:FLEET SUPPLIES, INC.

Address:250 MAHONING AVE

Box:83831

City:CLEVELAND

State:OH

ZIP:44101

Info Phone Num:216-621-5250

Emergency Phone Num:216-621-5250

CAGE:LO176

=== Contractor Identif

ication ===

Company Name:FLEET SUPPLIES INC

Address:250 MANONING AVE

Box:City:CLEVELAND

State:OH

ZIP:44113

Country:US

Phone:216-621-5250

CAGE:3M868

Company Name:FLEET SUPPLIES, INC.

Address:250 MAHONING AVE

Box:83831

City:CLEVELAND

State:OH

ZIP:44101

Phone:216-621-5250

CAGE:LO176

===== Composition/Information on Ingredients =====

Ingred Name:FUEL OIL ( MIDDLE DISTILLATE)

CAS:68334-30-5

RTECS #:HZ1800000

Fraction by Wt: 100%

Other REC Limits:HMIS 100 PPM/5 MG/M3

=====

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT. MOST  
HAZARDOUS EXPOSURE IS TO AIRBORN MIST OR OTHER ASPIRATION OF LIQUID  
INTO LUNGS. PROLONGED/REPEATED OVEREXPOSURE MAY CAUSE LIVER OR  
KIDNEY DAMAGE.

Explanation of Carcinogenicity:API HAS DONE STUDIES INDICATING THAT  
REPEATED OVEREXPOSURE MAY CAUSE CANCER  
IN MICE

Effects of Overexposure:EYE:MILD IRRITATION. SKIN:DRYING,DEFATTING WITH  
PROLONGED CONTACT. INHALED:HEADACHE,NAUSEA,CINFUSION,DROWINESS.  
ASPIRATION OF LIQUID MAY CAUSE CHEMICIAL PNEUMONITIS. INGESTED:G/I  
IRRITATION,NAUSEA,POS SIBLE VOMITING.

Medical Cond Aggravated by Exposure:NONE EXPECTED

=====  
First Aid Measures  
=====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED  
CLOTHING (LAUNDER BEFORE REUSE) AND THOROUGHLY WA  
SH AREA OF CONTACT  
WITH SOAP AND WATER. INHALED:REMOVE FROM EXPOSURE. RESUSCITATE OR  
GIVE OXYGEN IF NEEDED THEN GET MEDICAL ATTENTION. INGESTED:DO NOT  
INDUCE VOMITING. GET MEDICAL ATTENTION. IF ANY IRRITATION PERSISTS  
OR IS SEVERE,GET MEDICAL CARE.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:125F

Lower Limits:TCC

Upper Limits:1225F

Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL,WQRER FOG. WATER  
MAY BE INEFFE

CTIVE NAD MAY SPREAD FIRE IF IMPROPERLY USED.

Fire Fighting Procedures:USE SELF CONTAINED BREATNING  
APPARATUS,ESPECIALLY IN CLOSED AREAS. WATER SPRAY MAY BE USED TO  
COOL FIRE EXPOSED CONTAINERS AND EQUIPMENT.

Unusual Fire/Explosion Hazard:WHEN HEATED SUFFICIENTLY,VAPORS MAY FORM  
EXPLOSIVE MIXTURES WITH AIR. SATURATED NEWSPAPERS,RAG,ETC. MAY  
UNDERGO SPONTANEOUS COMBUSTION.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ELIMINATED IGN

ITION SOURCES. USE APPROPRIATE  
PROTECTIVE EQUIPMENT. CONTAIN LEAK. PREVENT LEAK FROM ENTERING  
SEWER WATER WAY,ETC. RECOVER AS LIQUID. REPORT SPILL IF APPROPRIATE  
Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL AREA AWAY FROM OXIDIZERS  
AND IGNITION SOURCES. DETACHED STORAGE PREFERRED. GROUND CONTAINERS  
DURING TRANSFER.

Other Precautions:"EMPTY" CONTAINERS MAY CONTAIN RESIDUE AND/OR FUMES  
WHICH EXPLOSIVE. DO NOT CUT,WELD,ETC.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT EXPECTED TO BE NECESSARY. USE NIOSH/MSHA  
RESPIRATOR IF PRODUCT IS MISTED OR IT TLV/PEL IS EXCEEDED.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TVL/PEL IF  
NORMAL ROOM VENTILATION IS IN SUFFICIENT.

Protective Gloves:RUBBER,PLASTIC,OR OTHER IMPERVIOUS

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES.

Other Protective Equipment:AS REQUIRED TO  
MINIMIZE SKIN CONTACT.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID  
UNNECESSARY CONTACT.

Supplemental Safety and Health

FLEET SUPPLIES PURCHASES PRODUCT FORM VARIOUS REFINERS THEN RESELLS IT  
USING THEIR OWN MSDS.

=====  
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:320F

Vapor Pres:0.4 MM

Vapor Density:4.70

Spec Gravity:0.88

Viscosity:NO

Evaporation Rate & Reference:SLOWER,THAN ETHER

Solubility in Water:NEGLIGIBLE

Ap

pearance and Odor: CLEAR, COLORLESS TO AMBER LIQUID, KEROSENE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: HEAT, IGNITION SOURCES

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE, LOCAL REGULATIONS.  
INCINERATION IS RECOMMENDED FOR DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.