

MFR	UNKNOWN/DEFENSE	CONSTRUCTION	S.CTR.	PROCURED	--
EXTINGUISHER,FIRE,VAPORIZING LIQUID -- 4210-01-143-5938					

===== Product Identification =====

Product ID:EXTINGUISHER,FIRE,VAPORIZING LIQUID  
MSDS Date:07/12/1989  
FSC:4210  
NIIN:01-143-5938  
MSDS Number: BGXKZ  
=== Responsible Party ===  
Company Name:MFR UNKNOWN/DEFENSE CONSTRUCTION S.CTR. PROCURED  
Box:3990  
City:COLUMBUS  
State:OH  
ZIP:43216-5000  
Country:U  
S  
Info Phone Num:614-238-3131  
Preparer's Name:DGSC-SLM/DOD HMIS  
CAGE:JO772  
=== Contractor Identification ===  
Company Name:DEFENSE CONSTRUCTION SUPPLY CENTER  
Address:NONE  
Box:3990  
City:COLUMBUS  
State:OH  
ZIP:43215-5000  
Country:US  
Phone:614-238-3131  
CAGE:16236  
Company Name:MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED  
Address:700 ROBBINS AVENUE  
Box:3990  
City:PHILADELPHIA  
State:PA  
ZIP:19111-5096  
Country:US  
Phone:215-697-2000  
CAGE:JO772

===== Composition/Information on Ingredients =====

=====

Ingred Name:BROMOTRIFLUOROMETHANE  
CAS:75-63-8  
RTECS #:PA5245000  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM  
Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:LC50=416 GMM/CUM (RAT)  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: ASPHYXIAN, CNS' & PULMONARY  
EFFECTS. SKIN IRRITANT. CHRONIC:NONE KNOWN.  
Effects of Overexposur  
e:INHAL:DIZZINESS,DISORIENTATION, IMPAIRED  
COORDINATION, NARCOSIS, NAUSEA, OR VOMITING, LIGHT-HEADEDNESS,  
GIDDINESS, BREATH SHORTNESS. CARDIAC ARRHYTHMIA W/UNCONSCIOUSNESS  
OR EVEN DEATH IN HI-CONC W/LON G EXPOSURES; SKIN/EYES: CONTACT W/  
LIQUID CAN CAUSE FROSTBITE, OR SKIN IRRITATION.  
Medical Cond Aggravated by Exposure:CARDIAC PROBLEMS. (PRODUCT IS AN  
ASPHYXIAN & CAN INDUCE CARDIAC MUSCLE SENSITIZATION TO  
CIRCULATINGH EPINEPHRINE-LIKE COMPOUNDS.)

=====

= First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR-GET MED ATTN & GIVE O\*2/CPR AS  
REQUIRED FOR SITUATION @ HAND;DONOT GIVE EPINEPHRINE OR SIMILAR  
DRUGS AS CATECOLAMINES INCREASE RISK OF ELICITING CARDIAC  
DYSRYTHMIAS. EYES/SKI N:FLUSH W/WATER-TREAT FOR FROSTBITE W/MEDICAL  
ATTN; INGEST:NOT LIKELY TO OCCUR.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:MATERIAL IS A FIRE EXTINGUISHANT & IS

NON-FLAMMABLE. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:USE SCBA' WHEN FIGHTING FIRES WHERE CHEMICALS  
ARE INVOLVED. SCBA MAY BE NEEDED IF HALON-1301 CONTAINER RUPTURES  
OR RELEASES MATERIAL IN HEAT OF FIRE.  
Unusual Fire/Explosion Hazard:IN HEAT OF FIRE, HALON-1301 CONTAINER  
EXPOSED TO INTENSE HEAT OF FIRE MAY RUPTURE & MATERIAL COMPOSITION  
MAY OCCUR.

===== Accidental Release Measures =====

Spill Release Procedures:EVA

CUATE AREA OF UNNEEDED PERSONNEL, VENTILATE  
AREA ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MIGHT COLLECT. COOL  
OR REMOVE HOT METAL SURFACES OR SOURCES OF NON-EXTINGUISHED FLAMES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE & HANDLE AS A LIQUIFIED  
COMPRESSED GAS IN DOT' APPROVED PRESSURE VESSELS AWAY FROM  
HI-TEMPERATURES.

Other Precautions:AVOID UNNECESSARY EXPOSURE TO HALON 1301! IN  
EMERGENCY, EXPOSURE SHOULD BE  
LIMITED TO: 0-7%, 15 MIN; 7-15%, 1  
MIN; 10-15%, 30 SEC; & FOR >15%, PREVENT EXPOSURE. SMALL CONC(5%)  
OF HALON EXTINGUISHES FLAMES BY CHEMICALLY INTERRUPTING COMBUSTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NECESSARY IF PROPER ENGINEERING  
CONTROLS ARE IN PLACE. IF PEL/TLV ARE EXCEEDED, USE POSITIVE  
PRESSURE AIR-SUPPLIED RESPIRATOR. REVIEW 29CFR1910.134  
INSTRUCTIONS/WARNINGS AS WELL AS NIOSH- RESPIRATOR DECISION LOG  
IC  
PUB87.108.

Ventilation:PROVIDE SUFFICIENT GENERAL/LOCAL EXHAUST VENTILATION IN  
PATTERN/VOLUME TO CONTROL INHALATION EXPOSURES BELOW PEL/TLV.

Protective Gloves:LINED BUTYL OR AS REQUIRED FOR TASK.

Eye Protection:CHEMICAL SPLASH TYPE OR AS REQ FOR TASK.

Other Protective Equipment:AS REQUIRED TO MINIMIZE EXPOSURE & MAXIMIZE  
INDIVIDUAL PROTECTION.

Work Hygienic Practices:OBSERVE PRECEDURES SET FORTH BY SAFETY/IH  
PERSONNEL FOR USE OF THIS MATERIAL FOR TASKS AT HAND.

Supplemental Sa

fety and Health

SMALL CONC(5%) OF HALON EXTINGUISH FLAMES BY CHEMICALLY INTERRUPTING  
COMBUSTION-NOT BY REPLACING O<sub>2</sub>. HOWEVER, VAPORIZATION OF EXCESSIVE  
AMTS CAN DEplete OR REPLACE O<sub>2</sub> NEEDED FOR BREATHING; GENERIC  
MSDS' ON NSN IDENTIFIED BY "DCSC". UPON RECEIPT OF A MFR'S MSDS  
UNDER THIS NSN, THE GENERIC WILL BE REMV.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-72F/-58C

Melt/Freeze Pt:M.P/F.P Text:-270F/-168C

Decomp Temp

:Decomp Text:900F/482C  
Vapor Pres:10738 @70F  
Vapor Density:5.14  
Spec Gravity:1.538  
Evaporation Rate & Reference:RAPID; REFERENCE UNK  
Solubility in Water:0.03 % 77F  
Appearance and Odor:COLORLESS LIQUID W/ SLIGHT ETHEREAL ODOR.  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ACTIVE METALS (EG. ALKALINE EARTH & ALKALINE EARTH METALS, POWDERED  
AL, ZN, BE, ETC.) & METAL HYDRIDES.  
Stability Condition to Avoid:FLAMES OR HOT SURFACES >900F CAN CAUSE  
DECOMPOSITION OF MATERIAL.  
Hazardous Decomposition Products:AT HI-TEMPS (>900F): HF, HBR, FREE BR,  
POSSIBLE CARBONYL HALIDES, & OXIDES OF BROMINE, FLUORINE, OR  
CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY W/ ALL FEDERAL, STATE & LOCAL REGULATION.  
RECLAIM MATERIAL IN A SUITABLE VAPOR RECOVERY SYSTEM/EQUIPMENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.