

INDUSTRIAL FLOOR FINISHES -- LIQUID POLISH -- 7930-00-266-7142

===== Product Identification =====

Product ID:LIQUID POLISH  
MSDS Date:05/19/1987  
FSC:7930  
NIIN:00-266-7142  
MSDS Number: BGXMR  
=== Responsible Party ===  
Company Name:INDUSTRIAL FLOOR FINISHES  
Address:605 SPRING STREET  
City:BEDFORD  
State:MA  
ZIP:01730  
Country:US  
Info Phone Num:508-667-5161  
Emergency Phone Num:508-667-5161 OR LOCAL POISON  
CENTER  
Preparer's Name:T. PITROLFFY  
CAGE:INDUS  
=== Contractor Identification ===  
Company Name:INDUSTRIAL FLOOR FINISHES  
Address:605 SPRINGS RD  
City:BEDFORD  
State:MA  
ZIP:01730  
Country:US  
Phone:1-617-667-5161  
CAGE:INDUS

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 17%  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: I

nhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE:PRIMARY EYE AND SKIN IRRITANT  
WITH CONTACT. CHRONIC: NOT SUFFICIENT DATA.  
Effects of Overexposure:HEADACHE,DIZZINESS AND NAUSEA.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER; SKIN:WASH WITH SOAP AND WATER, APPLY  
SKIN CREAM. INHALATION:REMOVE TO FRESH AIR, RESTORE BREATHING, CALL  
PHYSICIAN. INGESTION:DRINK WATER OR MILK, DO NOT INDUCE VOMITING.

C  
ALL POISON CONTROL.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:104F-40C  
Lower Limits:0.8  
Upper Limits:6.0  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO  
PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.  
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT. CLOSED CONTAINERS MAY  
EXPLODE IF EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION, SPRINKLE WITH  
ABSORBENT. FOG WITH WATER, FLUSH OR SCRAPE INTO RETAINING AREA OR  
CONTAINER. INCREASE VENTILATION. AVOID BREATHING VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN  
FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED  
CONTACT. KEEP CONTAINER CLOSED.  
Other Precautions:AVOID STATIC BUILD-UP. KEEP AWAY F  
ROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR  
CONCENTRATIONS ABOVE TLV.  
Ventilation:LOCAL AND MECHANICAL EXHAUST FROM LOWER LEVELS.  
Protective Gloves:USE RUBBER GLOVES.  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM.  
Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Tex

t:215F  
Vapor Pres:2  
Vapor Density:3.8  
Spec Gravity:1.1  
Evaporation Rate & Reference: