

INDUSTRIAL FLOOR FINISHES -- LIQUID POLISH -- 7930-00-266-7142

=====
Product Identification
=====

Product ID:LIQUID POLISH
MSDS Date:05/19/1987
FSC:7930
NIIN:00-266-7142
MSDS Number: BGXMR
=== Responsible Party ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRING STREET
City:BEDFORD
State:MA
ZIP:01730
Country:US
Info Phone Num:508-667-5161
Emergency Phone Num:508-667-5161 OR LOCAL POISON
CENTER
Preparer's Name:T. PITROFF
CAGE:INDUS
=== Contractor Identification ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRINGS RD
City:BEDFORD
State:MA
ZIP:01730
Country:US
Phone:1-617-667-5161
CAGE:INDUS

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 17%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

Routes of Entry: I

Inhalation: YES Skin: YES Ingestion: YES

Health Hazards Acute and Chronic: ACUTE: PRIMARY EYE AND SKIN IRRITANT WITH CONTACT. CHRONIC: NOT SUFFICIENT DATA.

Effects of Overexposure: HEADACHE, DIZZINESS AND NAUSEA.

=====
===== First Aid Measures =====

First Aid: EYES: FLUSH WITH WATER; SKIN: WASH WITH SOAP AND WATER, APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR, RESTORE BREATHING, CALL PHYSICIAN. INGESTION: DRINK WATER OR MILK, DO NOT INDUCE VOMITING.

C

ALL POISON CONTROL.

=====
===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: 104F-40C

Lower Limits: 0.8

Upper Limits: 6.0

Extinguishing Media: FOAM, CO2, DRY CHEMICAL.

Fire Fighting Procedures: WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT. CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE WITH ABSORBENT. FOG WITH WATER, FLUSH OR SCRAPE INTO RETAINING AREA OR CONTAINER. INCREASE VENTILATION. AVOID BREATHING VAPORS.

=====
===== Handling and Storage =====

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINER CLOSED.

Other Precautions: AVOID STATIC BUILD-UP. KEEP AWAY FROM CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV.

Ventilation: LOCAL AND MECHANICAL EXHAUST FROM LOWER LEVELS.

Protective Gloves: USE RUBBER GLOVES.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Tex

t:215F

Vapor Pres:2

Vapor Density:3.8

Spec Gravity:1.1

Evaporation Rate & Reference: