

INDUSTRIAL FLOOR FINISHES -- LIQUID POLISH A-A-15 -- 7930-00-721-8873

=====
Product Identification
=====

Product ID:LIQUID POLISH A-A-15
MSDS Date:05/01/1987
FSC:7930
NIIN:00-721-8873
MSDS Number: BGXNH
=== Responsible Party ===
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRING ST
City:BEDFORD
State:MA
ZIP:01730
Country:US
Info Phone Num:617-667-5161
Emergency Phone Num:617-667-5161 OR LOC
AL POISON CENTER
Preparer's Name:T. PITROFFY
CAGE:INDUS

==== Contractor Identification ====

Company Name:GSA/FEDERAL COMMERCIAL ITEM DESCRIPTION
Address:PROMULGATED BY GENERAL SERVICES ADMIN.
Box:City:WASHINGTON
State:DC
Country:US
CAGE:58536
Company Name:INDUSTRIAL FLOOR FINISHES
Address:605 SPRINGS RD
City:BEDFORD
State:MA
ZIP:01730
Country:US
Phone:1-617-667-5161
CAGE:INDUS

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #

:WJ8925000
Fraction by Wt: 17%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: PRIMARY EYE & SKIN IRRITANT
WITH CONTACT. INHALATION: MAY CAUSE HEADACHE, DIZZINESS & NAUSEA.
CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH WATER; SKIN: WASH WITH SOAP & WATER,
APPLY SKIN CREAM. INHALATION:REMOVE TO FRESH AIR,RESTORE
BREATHING,CALL PHYSICIAN. INGESTION:DRINK WATER OR MILK, DO NOT
INDUCE VOMITING-CALL POISON CONTROL.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:MIN 104F
Lower Limits:0.8
Upper Limits:6.0
Extinguishing Media:FOAM-CO2-DRY CHEMICAL.
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO
PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT,CLOSED CONTAINERS MAY
EXPLODE IF EXPOSED TO EXTREME HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION, SPRINKLE WITH
ABSORBENT. FOG WITH WATER,FLUSH OR SCRAPE INTO RETAINING AREA OR
CONTAINER. INCREASE VENTILATION AVOID BREATHING VAPORS.

=====
Handling and Storage
=====

=====
Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINER CLOSED.

Other Precautions:AVOID STATIC BUILD-UP.KEEP AWAY FROM CHILDREN.

=====
Exposure Controls/Personal Protection

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV.

Ventilation:LOCAL EXHAUST YES MECHANICAL-EXHAUST FROM LOWER LEVELS.

Protective

Gloves:USE RUBBER GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM.

Supplemental Safety and Health

NONE

=====
Physical/Chemical Properties

Boiling Pt:B.P. Text:215F

Vapor Pres:2

Vapor Density:3.8

Spec Gravity:1.1

Evaporation Rate & Reference:WATER 0.8

Solubility in Water:PARTIAL

Appearance and Odor:GREEN CREAMY LIQUID.

Percent Volatiles by Volume:74

=====
Stability and Reactivity Data

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:HEAT,SPARKS,OPEN FLAME & FIRE.

Hazardous Decomposition Products:THERMAL DECOMPOSITION PRODUCES FUMES
MAY YIELD CARBON MONOXIDE.

=====
Disposal Considerations

Waste Disposal Methods:INCINERATE OR DISPOSE OF IAW LOCAL,STATE AND FEDERAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN FUMES. DO NOT EXPOSE TO HEAT OR FLAME.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.