View NSN Online: https://aerobasegroup.de/nsn/8010-00-290-6645

Product ID: ENAMEL, ZN DUST, B15145 MSDS Date:04/26/1988 FSC:8010 NIIN:00-290-6645 **MSDS Number: BGXTL** === Responsible Party === Company Name: DAVLIN PAINT CO. Address:700 ALLSTON WAY Box:2308 City:BERKELEY State:CA ZIP:94702 Country:US Preparer's Name: PATRICIA SHAW CAGE:DO185 === Contractor Identificat ion === Company Name: DAVLIN PAINT CO INC Address:700 ALLSTON WAY Box:2308 City:BERKELEY State:CA ZIP:94702 Country:US Phone:510-848-2863 CAGE:3Z268 Company Name: DAVLIN PAINT CO. Address: P.O. BOX 2308 Box:2308 City:BERKELEY State:CA ZIP:94702 Phone:415-889-7098 CAGE:DO185

Ingred Name:VM&P NAPHTHA (LIGROINE) CAS:8032-32-4 RTECS #:OI6180000 Fraction by Wt: 20% Other REC Limits:125 PPM OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; 9192

Ingred Name:ZINC OXIDE CAS:1314-13-2 RTECS #:ZH4810000 Fraction by Wt: 15% Other REC Limits:FUMES OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:ZINC DUST CAS:7440-66-6 Fraction by Wt: 55% ACGIH TLV:15 MG/M3 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PETR OLEUM HYDROCARBONS & SYNTHETIC

LUBRICANTS POSE POTENTIAL HUMAN HEALTH RISKS WHICH VARY FROM PERSON TO PERSON. EXPOSURE TO LIQUIDS, VAPORS, MISTS OR FUMES SHOULD BE MINIMIZED. CHRONIC EXPOSURE MAY CAUSE DAMAGE TO CENTRAL NERVOUS SYS,RESPIRATORY SYS,LUNGS, EYES, SKIN, GASTROINTESTINAL TRACT,SPLEEN & KIDNEY.

Explanation of Carcinogenicity:PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIF TO CAUSE CANCER, OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

Effects of O

verexposure:INHAL:NASAL & RESPIRATORY

IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE.EYE: IRRITATIO N, TEARING, REDNESS & BLURRED VISION. SKIN: MODERATE IRRITATION, DEFATTING AND DERMATITIS. SKIN: SKIN ABSORPTI ON.

INGESTION: IRRITATION OF DIGESTIVE TRACT & SIGNS OF CENTRAL NERVOUS SYS DEPRESSION. ALSO AN ASPIRATION HAZARD.

Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA.

First Aid:EYE:FLUSH EYES W/WATER FOR 15 MIN LIFTING EYELIDS.OBTAIN MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING, WASH W/SOAP & WATER.IF IRRITATION PERSISTS,SEE A DOCTOR. INHALATION:REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED. INGESTION:GIVE WATER OR MILK AND TELEPHONE FOR MEDICAL ADVISE. DONOT TAKE PERSON VOMIT UNLESS DIRECTED BY MEDICAL STAFF. SEEK MEDICAL ATTENTION.

======

Flash Point Method:SCC Flash Point:105F/40.5C Lower Limits:1.0 Upper Limits:6.1 Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures:NFPA CLASS B EXTINGSRS DESIGNED TO EXTINGUISH FLAMMABLE LIQUID FIRE.APPROVD GAS MASK REQD FOR FIRE FIGHTING PERSNEL.WTR MAYBE INEFFECTIVE/BUT AS FOG FOR COOLING Unusual Fire/Explosion Hazard:VAPORS FORM EXPLOSIVE MIXTURE W/AIR BETWN LOWER/UPPER EXPLOSIVE LIMITS WHICH CAN BE IGNITED BY MANY SOURCES. ISOLATE FRO

M HEAT, ELEC EQUIP, SPARKS, OPEN FLAMES.

Spill Release Procedures: EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENTILATE AREA. EQUIP EMPLOYEES W/APPROPRIATE EQUIP. DIKE AROUND SPILLED AREA. COVER SPILL W/INERT ABSORBANT AND TRANSFER USING NON-S PARKING TOOLS.

Handling and Storage Precautions: STORE BELOW 80F IN CLOSED CONTAINE R.

STORE IN ORIGINAL CONTAINER. AVOID FLAME & HIGH TEMP. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS.

Other Precautions:DO NOT TAKE INTERNALLY, AVOID PROLONGED INHALATION. GROUND ALL CONNECTIONS, CONTAINERS, ETC. WHEN POURING OR TRANSFERRING TO MINIMIZE STATIC ELECTRICITY.USE NON-SPARKING TOOLS.

Respiratory Protection: WHEN SPRAYING MATERIAL USE NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK. WHEN USING IN P

OORLY VENTILATED

AND CONFINED SPACES, USE A FRESH-AIR SUPPLYING RESPIRATOR OR A SELF-CONTAINED BREATHING APPA RATUS.

Ventilation: GEN MECHANICAL OR LOCAL EXHAUST SHOULD BE SUITABLE TO KEEP VAPOR CONCENTRATIONS BELOW TLV.EQUIP MUST BE EXPLOSION PROOF. Protective Gloves: IMPERVIOUS GLOVES IS ADVISED.

Eye Protection: CHEMICAL SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT EXPOSURE OF SKIN.USE HEAD CAPS W

HENEVER POSSIBLE

Work Hygienic Practices: AFTER USING, WASH BEFORE EATING, TOILETING OR SMOKING.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY, AVOID PROLONGED INHALATION. GROUND ALL CONNECTIONS, CONTAINERS, ETC WHEN POURING OR TRANSFERRING TO MINIMIZE STATIC ELECTRICITY.USE NON-SPARKING TOOLS.

Boiling Pt:B.P. Text:306F Vapor Density:>AIR Spec Gravity:2.1 Evaporation Rate & amp; Reference:SLOWE THAN ETHER So Iubility in Water:NOT WATER SOLUBLE Appearance and Odor:PIGMENTED LIQUID. MILD SOLVENT ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR MONOXIDE, LOW MOLEULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

Waste Disposal Methods: KEEP OUT OF DRAINS, SEWERS, AND WATERWAYS. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing

this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.