

DOW CORNING CORPORATION -- 3145 RTV ADHESIVE SEALANT - CLEAR -- 8040-00-117-8510  
===== Product Identification =====

Product ID:3145 RTV ADHESIVE SEALANT - CLEAR

MSDS Date:09/11/1993

FSC:8040

NIIN:00-117-8510

MSDS Number: BGZYB

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:3901 SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48602-5601

Country:US

Info Phone Num:517-496-6000/5

17-496-5900

Emergency Phone Num:517-496-6000/517-496-5900

Preparer's Name:JACK L SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

===== Composition/Information on Ingredients =====

Ingred Name:HEXAMETHYLDISILAXANE, SILICA REACTION PRODUCT \*95-1\*

CAS:68909-20-6

Fraction by Wt: 22%

Ingred Name:METHYLTRIMETHOXYSILANE

CAS:1185-55-3  
RTECS #:VV4650000  
Fraction by Wt: 7%

Ingred Name:SILOXANES & SILICONES DI-ME HYDROXY-TERMINATED \*95-1\*  
CAS:70131-67-8

Ingred Name:DIMETHYLCYCLOPOLYSILOXANE  
CAS:69430-24-6

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:  
NOSE & THROAT IRRITATION, NERVOUS SYSTEM INJURY. INGESTIO  
N: MAY  
CAUSE DEATH.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, REDNESS, SWELLING, DROWSINESS,  
UNCONSCIOUSNESS, BLINDNESS.  
Medical Cond Aggravated by Exposure:ALLERGIC CONDITIONS.

=====  
===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH W/WATER FOR 15 MINS. SKIN: WIPE OFF &  
FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: IF  
CONSCIOUS, INDUCE VOMITING. LIE DOWN, KEEP WARM & COVER EYES TO  
EXC  
LUDE LIGH T. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:>212F  
Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM.  
Fire Fighting Procedures:WEAR A SELF CONTAINED BREATHING APPARATUS &  
PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:WHEN HEATED TO TEMPS >356F IN PRESENCE OF  
AIR, PRODUCT CAN FORM FORMALDEHYDE VAPORS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT & USE ABSORBENT MATERIAL TO  
TAKE CARE OF ANY OIL-LIKE RESIDUES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE