

BULK CHEMICALS DIVISION -- MIL-C-11796C CLASS I -- 8030-00-231-2354
===== Product Identification =====

Product ID:MIL-C-11796C CLASS I
MSDS Date:01/01/1987
FSC:8030
NIIN:00-231-2354
MSDS Number: BGZYW
=== Responsible Party ===
Company Name:BULK CHEMICALS DIVISION
Address:80 FIRST STREET
City:GRETNA
State:LA
ZIP:70053
Info Phone Num:(504) 362-3232
Emergency Phone Num:(504) 362-3232
CAGE:56921

===
Contractor Identification ===
Company Name:BULK CHEMICALS DISTRIBUTORS,INC
Address:80 FIRST STREET
City:GRETNA,
State:LA
ZIP:70053
Country:US
Phone:504-362-3232 DISCONNECTED(2-20-92)
CAGE:56921

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL
CAS:64742-52-5
RTECS #:PY8035000
Fraction by Wt: 10.15%
OSHA PEL:350 PPM
ACGIH TLV:2000 MG/CUM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES

Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING & DERMATITIS. EYES: CAN CAUSE MODERATE IRRITATION, REDNESS, TEARING. INHALATION: MIST/DUST CAN CAUSE DAMAGE TO NASAL & RESPIRATORY PASSAGES. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA, MOUTH & ESOPHAGUS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: PROLONGED/REPEATED CONTACT CAN CAUSE

MODERATE IRRITATION, DEFATTING & DERMATITIS. EYES: CAN CAUSE MODERATE IRRITATION, REDNESS, TEARING. INHALATION: MIST/DUST CAN CAUSE DAMAGE TO NASAL & RESPIRATORY PASSAGES. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA, MOUTH & ESOPHAGUS.

=====
===== First Aid Measures =====

First Aid:SKIN: WASH AREA W/SOAP & WATER. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. EYE: F

LUSH W/LARGE AMOUNT OF WATER. GET MED

ATT. INGESTION: DRINK 2 GLASSES OF WATER/INDUCE VOMITING. NEVER GIVE ANY THING BY MOUTH TO UNCONSCIOUS PERSON. GET MED ATT.

INHALATION: MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESP. KEEP PERSON WARM/QUIET.

=====
===== Fire Fighting Measures =====

Flash Point:350.0F

Extinguishing Media:REGULAR FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEA

R SCBA. WATER/FOAM CAUSE FROTHING WHICH CAN

BE VIOLENT/POSSIBLY ENDANGER LIFE OF FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL: SWEEP UP MATERIAL INTO PAPER. LARGE: PREVENT RUN-OFF TO SEWER, STREA

