

J. L. HOFFMAN CO., INC. -- SODIUM SILICATE SOLUTION -- 6810-00-240-2125

=====
Product Identification
=====

Product ID:SODIUM SILICATE SOLUTION

MSDS Date:09/18/1987

FSC:6810

NIIN:00-240-2125

MSDS Number: BHBTG

=== Responsible Party ===

Company Name:J. L. HOFFMAN CO., INC.

Box:8656

City:ALLENTOWN

State:PA

Country:18

Info Phone Num:NONE LISTED

Emergency Phone Num:215-432-4466

Preparer's Name:I. HADJ

ULOUKAS

CAGE:JO948

=== Contractor Identification ===

Company Name:J. L. HOFFMAN CO., INC.

Box:8656

City:ALLENTOWN

State:PA

ZIP:18105

Country:US

Phone:215-432-4466

CAGE:JO948

Company Name:LOCKHEED CORP LOCKHEED-GEORGIA CO DIV

Address:86 S COBB DR

Box:City:MARIETTA

State:GA

ZIP:30063

Country:US

Phone:404-494-4411

CAGE:98897

=====
Composition/Information on Ingredients
=====

Ingred Name:SODIUM SILICATE

CAS:6834-92-0

RTECS #:VV9275000

Fraction by Wt: 100%

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:EYES/CAUSES IRRITATION. SKIN/CAUSES
IRRITATION. INHALATION SPRAY MIST MAY DAMAGERESPIRATORY TRACT.
Explanation of Carcinogenicity:NONE LISTED
Effects of Overexposure:NONE LISTED
Medical Cond Aggravated by Exposure:NONE LISTED

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FO
R AT
LEAST 15 MIN. CALL PHYSICIAN. FLUSH SKIN WITH WATER

===== Fire Fighting Measures =====

Flash Point:NA
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:NA
Fire Fighting Procedures:NA
Unusual Fire/Explosion Hazard:NA

===== Accidental Release Measures =====

Spill Release Procedures:LESS THAN 100 GAL. MOP AND FLUSH TO SEWER WITH
PLENTY OF WATER. LARGE QUANTITIES: ISOLATE, DIKE & STORE DISCHARGED
MATERIAL, IF POSSIB
LE. OTHERWISE DISPERSE AND FLUSH WITH WATER
OBSERVE ENVIRONMENTAL PROTECTION REGULATIONS.
Neutralizing Agent:SEE ABOVE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH EYES, SKIN &
CLOTHING - WASH THOROUGHLY AFTER HANDLING. WASH CONTAMINATED
CLOTHING BEFORE RE-USE. KEEP CONTAINER CLOSED.
Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH A

APPROVED MIST RESPIRATOR WHERE SPRAY OCCURS.

Ventilation:NORMAL

Protective Gloves:RUBBER

Eye Protection:GOGGLES & FACE SHIELD

Other Protective Equipment:SAFETY SHOWER AND EYEWASH FOUNTAIN WITHIN DIRECT ACCESS.

Work Hygienic Practices:NONE LISTED

Supplemental Safety and Health
NONE LISTED

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Decomp Temp:Decomp Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.3-1/5 LIQ ONL

pH:11/13

Evaporation R

ate & Reference:NA

Solubility in Water:COMPLETE

Appearance and Odor:VISCIOUS LIQUID, COLORLESS TO HAZE, ODORLESS

Percent Volatiles by Volume:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

GELS WHEN MIXED WITH ACID.

Stability Condition to Avoid:FLAMMABLE HYDROGEN GAS MAY BE PRODUCED ON PROLONGED CONTACT WITH ALUMINUM, TIN, LEAD AND ZINC.

Hazardous Decomposition Products:HYDROGEN

===== Disposal Considerations =====

ons =====

Waste Disposal Methods:LESS THAN 100 GAL,: FLUSH TO SEWER WITH PLENTY OF WATER. LARGER QUANTITIES: NEUTRALIZE WITH DILUTE ACID AND LANDFILL SOLIDS ACCORDING TO LOCAL, STATE,FEDERAL REGULATIONS. FLUSH NEUTRAL LIQUID TO SEWER WITH PLENTY OF WATER

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr

essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.