

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS 44 BLACK 17038, ID742702 -- 8010-00-286-7725
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS 44 BLACK 17038, ID742702

MSDS Date:03/22/1988

FSC:8010

NIIN:00-286-7725

MSDS Number: BHCBJ

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316

-733-1361

Emergency Phone Num:316-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PP

M; 9192

Ingred Name:MINERAL SPIRITS
(VP 2 MM HG @ 20 DEG.C)
CAS:64475-85-0
RTECS #:PY8240000
OSHA PEL:500 PPM 2950 MG/CU.M
ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING:D
O NOT INDUCE VOMITING. GET

MED. ATTN. INHALATION: MOVE TO FRESH AIR,KEEP WARM/QUIET, GET MED
ATTN, EYE:FLUSH WITH LARGE AMOUNTS OF WATER. GET MED. ATTN, SKIN:
REMOVED CONTAMINATED CLOTHING . WASH AFFECTED AREA. NOTE TO
PHYSICIAN;OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF
SYMPTOMS & THE CLINICAL COND.

Explanation of Carcinogenicity:NONE LISTED

Effects of Overexposure:PROLONGED & REPEATED OCCUPATION OVEREXPOSURE TO
SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAG

E. DELIBERATE

CONCENTRATION & INHALING MAY BE FATAL. HIGH CONCENTRATIONS MAY
CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY
HEADACHES, DIZZINESS, NAUSEA AND CONFUSION.

Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:SWALLOWING DONOT INDUCE VOMITING. INHALATION REMOVE TO FRESH
AIR. EYE FLUSH WITHLARGE AMOUNTS OF WATER GET MEDICAL ATTN ON ALL
OF THE ABOVE. SKIN REMOVE CONTAM-INATED CLOTH

IN, WASH BEFORE

RE-USE. IF IRRITATION PERSISTS SEEK MED. ATTENTION. ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

===== Fire Fighting Measures =====

Flash Point: 102F/48.89C

Extinguishing Media: CLASS B FIRE EXTINGUISHERS FOR FLAMMABLE LIQ. FIRES. POLYMERFOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures: WEAR SCBA WATER MAY BE USED TO COOL EXPOSED CONT

AINERS TO PREVENT PRESURE BUILD UP, AUTO INGNITION, EXPLOSION WHEN EXPOSED TO HEAT.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT/ELEC.

EQUIP./SPARKS/FLAME. KEEP CONTAINERS CLOSED. OVEREXPSR TO DECOMPOSTION PRODUCTS MAY CAUSE A HEALTH HAZARD. OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. DIKE W/INERT MATERIAL. PUT IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL.

USE ONLY NONSPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS, GROUNDWATER W/SPILLED MATERIAL OR USED ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 95F. STORE LG QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.106. RCRA CLASSIFICATION WOULD BE D001.

Other Precautions: DO NOT TAKE INTERNALLY. DO NOT WELD, BRAZE, CUT ON EMPTY CONTAINERS. DO NOT REUSE ANY CONTAINERS. NEVER USE PRESSURE TO EMPTY.

DRUM IS NOT A PRESSURE VESSEL. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN RESTRICTED VENTILATION AREAS A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. IN OCNFINED AREAS USE A NIOSH/MSHA AIR SUPPLIED RESPIRATOR. REFER TO OSHA 29 CFR 1910.134

Ventilation: GENERAL DILUTION & LOCAL EXHAUST VENTILATION.

Protective Gloves: SOLVENT IMPERMEABLE GLOV

ES

Eye Protection:SAFETY SPECTACLES

Other Protective Equipment:NONE NEEDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280-388F

Vapor Density:< AIR

Evaporation Rate & Reference:> ETHER

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:AVOID EXCESSIVE HEAT

AND SOURCES OF

IGNITION

Hazardous Decomposition Products:BURNING,WELDING,CUTTING WILL PRODUCE
SMOKE, CARBON MONOXIDE AND DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN EPA PERMITTED FACILITY.

CONTAMINATED ABSORBANT MAY BE DISPOSED OF IN A HAZARDOUS WASTE
LANDFILL. DISPOSE IAW FEDERAL, STATE, AND LOCAL REGULATIONS.

DONOT INCINERATE

CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR
FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility

ty for the suitability of this information to their particular situation.