

KOPPERS CO. INC. -- ACRYLIC -- 8010-01-016-1488

=====
Product Identification
=====

Product ID:ACRYLIC
MSDS Date:03/01/1979
FSC:8010
NIIN:01-016-1488
MSDS Number: BHCNZ
=== Responsible Party ===
Company Name:KOPPERS CO. INC.
Address:5431 DISTRICT BLVD
City:LOS ANGELES
State:CA
ZIP:90040
Country:US
Info Phone Num:213-560-5700
Emergency Phone Num:213-560-5700
CAGE:GO941

==== Contractor Identification

====
Company Name:KOPPERS CO INC
Address:5431 DISTRICT BLVD
Box:City:VERNON
State:CA
ZIP:90040
Country:US
CAGE:71191
Company Name:KOPPERS CO. INC.
Address:KOPPERS BLDG
Box:City:PITTSBURGH
State:PA
ZIP:15219-1818
Country:US
CAGE:GO941

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SA

RA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:IRRITATION TO EYES, NOSE AND THROAT
NEAR OR ABOVE 25PPM FROM VAPORS. HIGHER CONCENTRATIONS CAUSE
DROWSINESS, FOLLOWED BY COMA. SKIN IRRITANT.
Effects of Overexposure:DROWSINESS,DIZZINESS,COMA.

=====
First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. CALL A
PHYSICIAN. IN CASE OF CONTACT, WASH
SKIN THOROUGHLY WITH SOAP AND
WATER. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF SWALLOWED, CALL
A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:23F/-5.00C
Extinguishing Media:WATER FOG, FOAM, DRY CHEMICALS, OR CARBON DIOXIDE.
Fire Fighting Procedures:USE AIR EQUIPMENT SUPPLIED FOR ENCLOSED AREAS.
COOL EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM

HEAT, SPARKS OR OPEN
FLAMES.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER ALL POSSIBLE, THEN WIPE UP WITH RAGS,
SAWDUST, ETC.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID FLAMES,
WELDING, SMOKING, SPARKS, OPEN LIGHT, ETC.

Other Precautions:MAINTAIN GOOD PERSONNEL HYGIENE. DO NOT USE IN
CONFINED AREAS, TANK OR PIT WITHOUT ADEQUATE VENTI
LATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE ORGANIC VAPOR CANISTER WHERE OXYGEN CONTENT
IS ADEQUATE AND THE VAPOR CONCENTRATION IS LESS THAN 2%, OTHERWISE
USE AIR SUPPLIED FACE MASKS.

Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL).

Protective Gloves:RUBBER GLOVES.

Eye Protection:GOGGLES.

Work Hygienic Practices:MAINTAIN GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:>AIR

Spec Gravity:9.4 LBS/GAL

Evaporation Rate & Reference:FAST

Solubility in Water:MODERATE

Percent Volatiles by Volume:67.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL APPLICABLE
REGULATIONS.

Disclaimer (provided with this information by the compiling agen

cies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.