

W.M. BARR & COMPANY -- PAINT REMOVER, 400063 -- 8010-00-160-5800

=====
Product Identification
=====

Product ID:PAINT REMOVER, 400063

MSDS Date:07/07/1989

FSC:8010

NIIN:00-160-5800

MSDS Number: BHCYH

=== Responsible Party ===

Company Name:W.M. BARR & COMPANY

Address:2105 CHANNEL AVENUE

Box:1879

City:MEMPHIS

State:TN

Country:US

Info Phone Num:901-775-0100

Emergency Phone Num:1-800-238-2672

Preparer

's Name:TIM HERSBERGER

CAGE:91522

=== Contractor Identification ===

Company Name:KLEAN-STRIP DIV BARR W M AND CO

Address:2105 CARNES AVE

Box:1879

City:MEMPHIS

State:TN

ZIP:38114

Country:US

Phone:901-775-0100

CAGE:25451

Company Name:W.M. BARR & COMPANY/KLEAN-STRIP, DIVISION OF

Address:2105 CHANNEL AVENUE

Box:1879

City:MEMPHIS

State:TN

ZIP:38101

Country:US

Phone:901-775-0100

CAGE:91522

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLENE CHLORIDE (SARA III)

C

AS:75-09-2
RTECS #:PA8050000
Fraction by Wt: < 80%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: < 10%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: < 5%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: < 5%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LONG TERM EFFECTS: METHYLENE CHLORIDE
HAS CAUSED CANCER IN CERTAIN LAB ANIMAL TESTS. RISK TO YOUR
HEALTH DEPENDS ON LEVEL AND DURATION OF EXPOSURE.PO
LONGED
ORREPEATED CONTACT MAY CAUSE DERMATITIS. R EPORTS HAVE ASSOCIATED
PROLONGED/REPEATDOVEREXPOSURE TO SOLVENTS
W/NEUROLOGICAL/PHYSIOLOGICAL DAMAGE.CAUSES BLOOD DISORD
Effects of Overexposure:IF INHALED: DIZZINESS, HEADACHE, NAUSEA,
WATERING OF EYES AND IRRITATION OF REPIRATORY TRACT. MY CAUSE
INCREASE IN CARBOXYHEMOGLOBIN LEVELS, DEPRESSION OF CENTRAL
NERVOUS SYSTEM, PARESTHESIAS OF EXTREMITIES, IRREGULAR HEARTBEAT
AND UN-CONSCIOUSNESS. INGESTION:GASTROINTEST

INAL

IRRITATION, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure: DISEASES OF THE SKIN, LIVER, KIDNEYS AND CARDIO- VASCULAR SYSTEM.

=====
First Aid Measures
=====

First Aid: INHALATION: MOVE TO FRESH AIR. GIVE CPR AND/OR OXYGEN WHEN NEEDED. GET MEDICAL ASSISTANCE. INGESTION: CALL HOSPITAL EMERGENCY ROOM, POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY FOR INSTRUCTIONS. SKIN CONTACT: WASH WITH SOAP AND LARGE QUANTITIES OF WATER AND SEEK MEDICAL ATTENTION IF IRRITATION FROM CONTACT PERSISTS. EYE CONTACT: FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MIN. CALL DR.

=====
Fire Fighting Measures
=====

Lower Limits: 12

Extinguishing Media: USE CARBON DIOXIDE, DRY POWDER OR FOAM.

Fire Fighting Procedures: SELF-CONTAINED RESPIRATORY PROTECTION SHOULD BE PROVIDED FOR FIREFIGHTERS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL W/ WATER SPRAY TO PREVENT PRESSURE

Un

usual Fire/Explosion Hazard: KEEP CONTAINER TIGHTLY CLOSED. CONTACT OF LIQUID OR VAPOR W/ FLAME OR HOT SURFACE WILL PRODUCE TOXIC GASES AND A CORROSIVE RESIDUE THAT WILL CAUSE METAL DETERIORATION

=====
Accidental Release Measures
=====

Spill Release Procedures: AVOID BREATHING VAPORS. VENTILATE AREA. FLUSH LRG. SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS WITH LARGE QUANTITIES OF WATER. SMALL SPILLS CAN BE ABSORBED BY APPROPRIATE INERT ABSORBENT.

=====
Handling and Storage
=====

Handling and Storage Precautions: DO NOT STORE NEAR FLAMES OR AT ELEVATED TEMPERATURE

Other Precautions: READ CAREFULLY ALL CAUTIONS AND DIRECTIONS ON PRODUCT LABEL BEFORE USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTY. DISPOSE OF EMPTY CONTAINER ACCORDING TO LOCAL REGULATIONS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH ADEQUATE VENTILATION UNDER ENGINEE AIR CONTROL SYSTEMS. FOR OCCASIONAL USE WHERE ENGINEERED AIR CONTROL IS NOT FEASIBLE, USE NIOSH APPROVED RESPIRATORS .

Ventilation:ADEQUATE VENTILATION MUST BE PROVIDED. SEE RESPIRATORY PROTECTION ABOVE.

Protective Gloves:USE IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES

Other Protective Equipment:VARYING APPLICATION METHODS CAN DICTATE USE OF ADDITIONAL PROTECTIVE SAFETY EQUIPMENT, SUCH AS IMPERMEABLE APRONS, ETC

Work Hygienic Practices:BEFORE REUSE, THOROUGHLY CLEAN ANY CLOTHING OR PROTECTIVE EQUIPMENT WHICH HAS BEEN CONTAMINATED BY PRIOR USE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:103 - 340F

Vapor Density:> AIR @20C

Spec Gravity:1.180 @ 68F

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:MODERATE

Appearance and O

lor:WHITE, SOLVENT ODOR

Percent Volatiles by Volume:99.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE HYDROGEN CHLORIDE & SMALL QUANTITIES OF PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH STATE, LOCAL, AND FEDERAL REGULATIONS.

Disclaimer (pro

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.