

EVERSEAL MANUFACTURING CO., INC. -- SPAR VARNISH PHENOLIC -- 8010-00-234-5176

===== Product Identification =====

Product ID:SPAR VARNISH PHENOLIC

MSDS Date:03/19/1986

FSC:8010

NIIN:00-234-5176

MSDS Number: BHDCJ

=== Responsible Party ===

Company Name:EVERSEAL MANUFACTURING CO., INC.

Address:475 BROAD AVENUE

City:RIDGFIELD

State:NJ

ZIP:07657

Country:US

Emergency Phone Num:201-943-4986

CAGE:EO432

=

== Contractor Identification ==

Company Name:EVERSEAL MANUFACTURING CO., INC.

CAGE:EO432

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 52%

OSHA PEL:NA

ACGIH TLV:NA

Ingred Name:LINSEED OIL

Fraction by Wt: 5%

OSHA PEL:NA

ACGIH TLV:NA

Ingred Name:MINERAL SPIRITS

VAPOR PRESSURE 2, 5G/K

G (ORAL)  
CAS:64742-88-7  
Fraction by Wt: 42%  
ACGIH TLV:120 PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Effects of Overexposure:SKIN: DRYING EYES: IRRITATION  
INHALATION: MAY CAUSE ANESTHESIA,  
HEADACHE, DIZZINESS, NAUSEA, UPPER RESPIRATORY IRRITATION.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION  
IF NECESSARY. CALL A PHYSICIAN.  
SKIN: WASH WITH MILD SOAP & WATER.  
APPLY A MILD CREAM. IN SEVERE CASES CONTACT A PHYSICIAN.  
INGESTION:  
CALL A PHYSICIAN

=====  
Fire Fighting Measures  
=====

Flash Point:105F/40.56C  
Upper Limits:0.7  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING MEDIUM

=====  
Accidental Release Measures  
=====

Spill Release Procedures:FLUSH WITH WATER INTO RETAINING AREA OF  
CONTAINER.AVOID SPARKS, FIRE OR HOT METAL SURFACES. SMALL  
QUANTITIES MAY BE ABSORBED ONTO AN APPROPRIATE ABSORBANT.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP COOL, AWAY FROM SOURCES OF  
IGNITION, ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED PERSONAL  
CONTACT.  
Other Precautions:NPCA/HMIS RATING 3,2,0,H

=====  
Exposure Controls/Personal  
=====

nal Protection =====

Respiratory Protection:CARTRIDGE RESPIRATOR OR MASK

Ventilation:LOCAL EXHAUST IS SUFFICIENT TO KEEP WORKING ROOM CONCENTRATION BELOW THE TLV

Protective Gloves:IMPERMEABLE

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:APRON, BARRIER CREAM

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:326-387F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percen

t Volatiles by Volume:56

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, FIRE

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.