View NSN Online: https://aerobasegroup.de/nsn/8010-00-246-6116

Product ID:MINERAL SPIRITS, TT-T-291F, TYPE 1

MSDS Date:10/01/1986

FSC:8010

NIIN:00-246-6116

MSDS Number: BHDCZ === Responsible Party === Company Name:CSD, INC. Address:#5 HACKBERRY

City:CUT & SHOOT

State:TX ZIP:77302 Country:US CAGE:KO005

=== Contractor Identification === Company Name: CSD INC. (PR E 1985 NAME: MATHEWS, INC) Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

Company Name: CSD, INC. Address: 5 HACKBURY ST

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone:409-756-1065

CAGE:KO005

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS REGULAR

CAS:64741-41-9 Fraction by Wt: 35% ACGIH TLV:500 PPM

Ingred Name:66/3 MINERAL SPIRITS

CAS:64742-88-7 Fraction by Wt: 65%

ACGIH TLV

=========== Hazards Identification ============
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure:VAPORS MIGHT AFFECT CONTROL OF NERVOUS SYSTEM AND CAUSE RESPIRATORY IRRITATION. ADVANCED TEMPERATURES WOULD INCREASE THIS HAZARD. ANESTHESIA IN HIGH CONCENTRATNEYE: IRRITANT
======================================
First Aid:EYE: WASH GENTLY W/PLENTY WTR FOR 15 MINS. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTH & WASH W/SOAP & WATER. SEEK MEDICAL ATTENTION. INHAL: SEEK AIR FREE OF VAPORS. IF BREAT HING STOPS GIVE ARTIFICIAL RESPIRATION& SEEK MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, UNLESS DIRECTED BY PHYSICIAN. GET IMMEDIATE MEDICAL ATTENTION AND/OR ADVICE.
======================================
Flash Point Method:TCC Flash Point:105F/40.56C Lower Limits:6.0 Upper Limits:0.9 Extinguishing Media:MECHANICAL FOAM, DRY CHEMICAL, WATER FOG, CO2 Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS. STRAIGHT WATER STREAM WOULD SPREAD OIL FIRE. Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES.
========= Accidental Release Measures ==========
Spill Release Procedures:AVOID ALL SOURCES OF IGNITION. STAY UPWIND, COLLECT & DISPOSE OF SPILLS. STOP DISCHARGE IF POSSIBLE. COVER W/INERT MATERIAL. USENONSPARKING TOO LS FOR CLEANUP. KEEP OUT OF SEWERS, WATERWAYS, AND DRAINS.
=========== Handling and Storage ============
Handling and Storage Precautions: COMPLY WITH LOCAL FIR REGULATIONS. HANDLE AS CLII, COMBUSTIBLE LIQUID. Other Precautions: CONTACTS FIRE AUTHORITIES, NOTIFY HEALTH/POLLUTION CONTROL AGENCIES.
======= Exposure Controls/Personal Protection ========
Respiratory Protection:SELF CONTAINED BREATHING APPARATUS, WITH ADEQUATE VENTILATION. Ventilatio

:100 PPM

n:VENTILATE TO FIRE SAFE AREA. Protective Gloves:RECOMMENDED Eye Protection:GOGGLES Other Protective Equipment:IMPERMEABLE APRON, EYE WASHES, & SHOWERS AVAILABLE IN WORK AREAS. Supplemental Safety and Health NK
======== Physical/Chemical Properties =========
Boiling Pt:B.P. Text:310-405F Vapor Pres:1.8 @ 60F Vapor Density:5.05 Spec Gravity:.7741 Evaporation Rate & Description Rate &
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS, OR BASES & SELECTED AMINES. Stability Condition to Avoid:NA
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agen cies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.