View NSN Online: https://aerobasegroup.de/nsn/6830-00-261-7445

BUTANE, INC. -- PROPANE -- 6830-00-261-7445

Product ID: PROPANE MSDS Date:01/01/1987 FSC:6830 NIIN:00-261-7445 MSDS Number: BHDDR === Responsible Party === Company Name:BUTANE, INC. Address:2650 N. 35TH AVENUE City:PHOENIX State:AZ ZIP:85009 Country:US Info Phone Num:602-272-2344 CAGE:AZTEC === Contractor Identification === Company Name:BUTANE, INC. Address:2650 N . 35TH AVENUE Box:City:PHOENIX State:AZ ZIP:85009 Country:US CAGE:AZTEC Ingred Name: PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 100% OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIANT; 9192

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:LIQUID CAN CAUSE FREEZE BURNS SIMILAR TO

FROSTBITE IF CONTACT WITH SKIN OCCURS. LARGE CONCENTRATIONS OF VAPOR IN ATMOSPHERE CAN CAUSE ASPHYXIATION DUE TO OXYGENDISPLACEMENT. INHALATION OF SMALLER QUAN TITIES OF FAPOR CAN CAUSE RESPIRATORYIRRITATION, DIZZINESS, NAUSEA OR DROWSINESS.

First Aid:MEDICAL ATTENTION MANADATORY. EYE CONTACT: FLUSH WITH WATER. SKIN CONTACT: IF FREEZE BURN OCCURS, REMOVE CONTAMINATED CLOTHES, ETC. IMMERSE BURNED

AREA IN WARM WATER, NOT HOT. KEEP IMMERSED, GET MEDICAL ATTENTION. INHALATION: REMOVEVICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING GIVE CPR, IF UNCONSCIOUS SEEK IMMED MEDICAL ATTENTION, IF BREATHING IS LABORED, GIVE SUPPLEMENTAL OXYGEN.

Flash Point:-156F

Lower Limits:2.1%

Upper Limits:9.5%

Extinguishing Media:DRY CHEMICAL, FOAM OR CO2 FOR SMALL FIRES. STOP FLOW OF GAS FIRST.

Fire Fighting Procedure

S:EVACUATE AREA. NOTIFY FIRE DEPT. SHUT OFF

SOURCE OF GAS, IF POSSIBLE. ALLOW FIRETO BURN UNTIL GAS FLOW SHUT OFF. WATER COOL EXPOSED EQUIPMENT.

Unusual Fire/Explosion Hazard:PRODUCTS OF COMBUSTION MAY YIELD CARBON MONOXIDE. UNCONTROLLED VAPORS SPREAD RAPIDLY, ARE HEAVIER THAN AIR AND ARE EXTREMELY FLAMMABLE.

Spill Release Procedures: PRODUCT IS EXTREMELY FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. EVA

CUATE AREA. IF POSSIBLE, RE- MOVE LEAKING

CONTAINER TO SAFE AREA. STOP FLOW OF GAS OR ALLOW VAPOR TO DISPERSE IN SAFE AREA. USE WATER SPRAY TO HELP DILUTE VAPOR CONCENTRATION.

Handling and Storage Precautions:STORE/USE WITH ADEQUATE
VENTILATION.KEEP AWAY FROMHEAT AND IGNITION SOURCES. STORE
CYLINDERS IN UPRIGHT POSITION. PROTECT FROM DAMAGE.
Other Precautions:DEEP CONTAINER VALVE CLOSED AND PLUGGED WHEN NOT

IN USE. INSTALL PROTECTIVE CAPSWHEN CYLINDERS ARE NOT CONNECTED FOR USE.

Respiratory Protection:USE A NIOSH-APPROVED RESPIRATOR IF AREA IS THOUGHT TO CONTAIN UNKNOWN CONENTRA- TIONS OF GAS. Ventilation:USE ADEQUATE VENTILATION TO MAINTAIN EXPOSURES BELOW RECOMMENDED LIMITS. Protective Gloves:PROPANE RESISTANT GLOVES Eye Protection:SAFETY GOGGLES OR SAFETY GLASSES Supplemental Safety and Health NK

=====

HCC:G2 Boiling Pt:B.P. Text:-44F Vapor Pres:*SEE BELOW Vapor Density:1.5 Spec Gravity:0.507 Solubility in Water:INSOLUBLE Appearance and Odor:COLORLESS LIQUEFIED PETROLEUM GAS. PROPANE SOLD FOR FUEL CONTAINS A FOUL SMELL. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:NK *VAP PRE S: 208 PSIG (MAX) @ 100F Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN CAUSE CARBON MONOXIDE.

Waste Disposal Methods:DISPOSE OF GAS ONLY BY CONTROLLED BURNING IN COMPLIANCE WITH LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner

whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.