

CON-LUX COATINGS, INC. -- ENAMEL SEMI GLOSS RUST INHIBITING 24084 OD -- 8010-00-290-6648  
===== Product Identification =====

Product ID:ENAMEL SEMI GLOSS RUST INHIBITING 24084 OD

MSDS Date:05/12/1989

FSC:8010

NIIN:00-290-6648

MSDS Number: BHDJM

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMAGDE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Nu

m:(206) 287-4000

Emergency Phone Num:(206) 287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: >1%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction

by Wt: >1%  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:ZINC OXIDE  
CAS:1314-13-2  
RTECS #:ZH4810000  
Fraction by Wt: 4%  
OSHA PEL:15MG/M3 TDUST/5 FUME  
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:LEAD ORTHO-PLUMBATE  
CAS:1314-41-6  
Fraction by Wt: >1%  
OSHA PEL:0.2 MG/M3

Ingred Name:LEAD CHROMATE  
CAS:1344-37-2  
Fraction by Wt: 15%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:TALC (CONTAINING NO ASBESTOS)  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: >1%  
OSHA PEL:2  
MG/M3 RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 3%  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 1%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health

Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:SKIN/EYE: IRRITATION MAY OCCUR WITH OVEREXPOSURE. INHALATION: BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHE,NAUSEA, AND DIZZINESS.

=====  
===== First Aid Measures =====

First Aid:SKIN: WASH AFFECTED AREAS WITH SOAP & WATER. REMOVE

CONTAMINATED CLOTHING. CONSULT A PHYSICIAN IF IRRITATION PERSISTS. EYE: FLUSH IMMEDIATELY W/COPIOUS QUANTITIES OF WATER FOR 15 MINS. CONSULT A PHYSICIAN. INHAL: REMOVE TO FREESH AIR. RESTORE RESPIRATION IF NECESSARY. TREAT SYMPTOMATICALLY. INGEST: DRINK 1-2GLASSES OF WATER TO DILUTE.DONOT INDUCE VOMITING.CONSULT A PHYSICIAN IMMEDIATELY

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:80F/26.67C

Upper Limits:1.0-2.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST

Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY.

Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENTS. DO NOT USE IN AREAS WHERE SPARKS OR OPEN FLAMES AREPRESENT.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL W/ABSORBENT MATL & PUT IN

TO VAPOR TIGHT CONTAINERS.PREVENT MATL FROM CONTACTING ANY WATER SOURCES OR SEWERS LEADING TO SURFACE WATERS. WEAR APPROPRIATE PROTECTION EQUIP AND APPROVED RESPIRATOR.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS DESIGNED TO COMPLY W/ANSI/NFPA 30 FLAMMABLE AND COMBUSTIBLE LIQUIDS CODE.

Other Precautions:GROUND CONTAINERS WHEN POURING LIQUIDS/POWDERS TO AVOID STATIC CHARGE BUILD UP. PROVIDE ADEQUATE VENT

ILATION OR

RESPIRATORY PROTECTION TO REMOVE DECOMPOSITION PRODUCTS DURING WELDING OR FLAME CUTTING COATED SURFACES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/OPEN AREAS USE APPROVED RESPIRATOR. IN RESTRICTED VENTILATION AREAS USE APPROVED RESPIRATOR.

Ventilation:SUFFICIENT VENTILATION IN VOLUME AND PATTERN SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT CONCENT. BELOW CURRENT OSHA.

Protective Gloves:IMPERVIOUS TYPE

Eye Protection:

SAFETY GLASSES/TO PROTECT AGAINST SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOMS.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:148-323F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:57.67

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS

Stability Condition to Avoid:EXTREME HEAT, SPARKS, OR OPEN FLAMES

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED

HEATED

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formul

ated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.